




BRAVO-85-RTLA2



Product specification

INTERIOR RECESSED DOWNLIGHTS



80

Technical Specification

Article number	2118.651F-ACOT-36		
LED Consumption	14W		
Fixture Consumption	-		
Current / Voltage	350mA / 38.4Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1139lm	1193lm	1282lm
Delivered Lumen	-	934lm	-
Beam Angle available	15°/24°/50° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	0~30° / 0~355°	Baffle	Aluminum die cast
Operating temperature	0~35°C	Baffle Color available	white / black
Average Failure Time	-		


Accessories

SG7-1
Striped glassH7-1
Honeycomb louverDS7-1
Diffusion sheetWG7-1
Woven glassACOT-82
MR16 Accessory kitsACOT-83
GU10 Accessory kitsPJ-0079
MR16&GU10 Accessory


Photometric




h(m)	D(m)	E(lx)
15°		
1.0	0.25	9104
2.0	0.50	2276
3.0	0.74	1012
4.0	0.99	569
5.0	1.24	364



h(m)	D(m)	E(lx)
24°		
1.0	0.45	4890
2.0	0.90	1223
3.0	1.34	543
4.0	1.79	305
5.0	2.24	195



h(m)	D(m)	E(lx)
36°		
1.0	0.65	2704
2.0	1.30	675
3.0	1.94	300
4.0	2.59	169
5.0	3.23	108



h(m)	D(m)	E(lx)
50°		
1.0	0.84	1654
2.0	1.68	413
3.0	2.52	183
4.0	3.36	103
5.0	4.19	66

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.