




STAR-50-RTLF2



Product specification

INTERIOR RECESSED DOWNLIGHTS



52

Technical Specification

Article number	2118.659F-ACOT-97		
LED Consumption	10W		
Fixture Consumption	-		
Current / Voltage	250mA / 36.5Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	871lm	913lm	981lm
Delivered Lumen	-	697lm	-
Beam Angle available	20°/25°/35°/50° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time		Baffle Color available	white / black

Accessories

ACHO-18
honeycomb louver
+PC sheetSG-002
Striped Glass

Photometric



h (m)	D (m)	E (lx)
50°		
1.0	0.91	1065
2.0	1.81	266
3.0	2.72	118
4.0	3.64	66
5.0	4.53	42

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.