




STAR-50-RTLA2



Product specification

INTERIOR RECESSED DOWNLIGHTS



52

Technical Specification

Article number 2118.660F-ACOT-97

LED Consumption 10W

Fixture Consumption -

Current / Voltage 250mA / 36.5Vdc

CRI 90+

CCT 2700K 3000K 4000K

LED Lumen ¹ 871lm 913lm 981lm

Delivered Lumen - 642lm -

Beam Angle available 20°/25°/35°/40° (Lens)

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Freqency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character

Products Standard	IEC 60598-1 IEC 62031		Luminaire Trim Optics	Aluminum die cast Aluminum die cast PMMA Lens
Insulation	CLASS II		Heat sink	Forged aluminum
Protection	IP44		Fixture color available	white / black
Tilt / Rotate	0~30° / Non		Baffle	Aluminum die cast
Operating temperature	0~35°C		Baffle Color available	white / black
Average Failure Time				

Accessories

ACHO-18
honeycomb louver
+PC sheetSG-002
Striped Glass

Photometric



h(m)	D(m)	E(lx)
35°		
1.0	0.66	1566
2.0	1.31	391
3.0	1.97	174
4.0	2.62	97
5.0	3.28	62

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.