




GAGA-75-RTLF2



Product specification

INTERIOR RECESSED DOWNLIGHTS



85

Technical Specification

Article number	2118.661-ACOT-36		
LED Consumption	14W		
Fixture Consumption	15W		
Current / Voltage	350mA / 38.3Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1139lm	1193lm	1282lm
Delivered Lumen	-	945lm	-
Beam Angle available	15°/24°/36°/50° (Lens)		

Driver Technical Specification (Remoted)


Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Steel
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	None / None	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	PC
Average Failure Time		Baffle Color available	white / black / Gold

Accessories

Photometric

SG7-1
Striped glassH7-1
Honeycomb louverDS7-1
Diffusion sheetWG7-1
Woven glass

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.