




SUNTEC



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	\square =43 x 43mm
Dimension	D= \square 40 x H= 72mm

**Technical description**

Article number	1068.168		
LED Consumption	3W		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	1m	160lm	1m
Øsystem ^{*3}	-	-	-
Voltage	4.3V		
Reflector	20°		
CRI	90+		
Driver	Remoted, I/P 100-240V AC , 50/60HZ O/P: Constant Current 700mA		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

Materials

Luminaire	steel bezel and housing
Reflector	anodized aluminum
Heat sink	aluminum die cast
Bezel color available	white/black
Baffle color available	white/black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

