




STARLUX-FLAT-3-STA2



Product specification

INTERIOR COMBO LIGHTS



Technical Specification

Article number	2214.411-3-ACOT-97		
LED Consumption	10W X3		
Fixture Consumption	30W		
Current / Voltage	250mA / 18v*3		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen *1	871lm x3	913lm x3	981lm x3
Delivered Lumen	-	-	-
Beam Angle available	15°/24°/36°/50° (Lens)		
Driver Technical Specification (Remoted)			
Driver Brand	-	Driver Model	-
Input voltage / Freqency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character	Materials
Products Standard	IEC 60598-1
	IEC 62031
Insulation	CLASS III
Protection	IP44
Tilt / Rotate	0~30° / 0~355°
Operating temperature	0~35°C
Average Failure Time	Baffle Color available
	white / black

Accessories

ACHO-18
honeycomb louver
+PC sheetSG-002
Striped Glass

Photometric

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.