



STAR-50-EYE-STAS




Product specification

**INTERIOR COMBO LIGHTS**

| Technical Specification                  |                        |                          |       |
|------------------------------------------|------------------------|--------------------------|-------|
| Article number                           | 2214.412-1-ACOT-96     |                          |       |
| LED Consumption                          | 7W                     |                          |       |
| Fixture Consumption                      | -                      |                          |       |
| Current / Voltage                        | 350mA / 17.8Vdc        |                          |       |
| CRI                                      | 90+                    |                          |       |
| CCT                                      | 2700K                  | 3000K                    | 4000K |
| LED Lumen *1                             | 618lm                  | 656lm                    | 716lm |
| Delivered Lumen                          | -                      | -                        | -     |
| Beam Angle available                     | 15°/24°/36°/50° (Lens) |                          |       |
| Driver Technical Specification (Remoted) |                        |                          |       |
| Driver Brand                             | -                      | Driver Model             | -     |
| Input voltage / Frequency range          | -                      | Output Current / Voltage | -     |
| Dimming / Flicker                        | -                      | Certification            | -     |
| Power Factor                             | -                      | Warranty                 | -     |

| Technical character   |                    | Materials               |                   |
|-----------------------|--------------------|-------------------------|-------------------|
| Products Standard     | IEC 60598-1        | Luminaire               | Aluminum die cast |
|                       | IEC 62031          | Trim                    | Aluminum die cast |
| Insulation            | CLASS III          | Optics                  | PMMA Lens         |
| Protection            | IP44               | Heat sink               | Forged aluminum   |
| Tilt / Rotate         | 0~30° / 0~355°     | Fixture color available | white / black     |
| Operating temperature | 0~35°C             | Baffle                  | Aluminum die cast |
| Average Failure Time  | L70(11k) >61000(h) | Baffle Color available  | white / black     |

Accessories



ACHO-18  
honeycomb louver  
+PC sheet

SG-002  
Striped Glass

Photometric

Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.