




EDELWEISS-W21



## Product specification

## INTERIOR RECESSED WALL LIGHT



## Technical Specification

|                         |               |        |
|-------------------------|---------------|--------|
| Article number          | 2215.108      |        |
| LED Consumption         | 22W           |        |
| Fixture Consumption     | -             |        |
| Current / Voltage       | 550mA / 36Vdc |        |
| CRI                     | 90+           | 80+    |
| CCT                     | 3000K         | 3000K  |
| LED Lumen <sup>*1</sup> | -             |        |
| Delivered Lumen         | 1998lm        | 2324lm |
| Beam Angle available    | 75°           |        |

## Driver Technical Specification (Built-in)


|                                |                      |                          |                            |
|--------------------------------|----------------------|--------------------------|----------------------------|
| Driver Brand                   | LiFud                | Driver Model             | LF-GMR020YSII(G3)          |
| Input voltage / Freqency range | 220-240Vac / 50/60Hz | Output Current / Voltage | 550mA / 33-42Vdc           |
| Dimming / Flicker              | Non / Free           | Certification            | ENEC / CB / CE / RCM / CCC |
| Power Factor                   | >0.92                | Warranty                 | 5years                     |

| Technical character   |                    | Materials |                    |
|-----------------------|--------------------|-----------|--------------------|
| Products Standard     | IEC 60598-1        | Luminaire | Extruded aluminum  |
|                       | IEC 62031          |           | Aluminum die cast  |
| Insulation            | CLASS II           | Reflector | Aluminum reflector |
| Protection            | IP20               | Glass     | glass              |
| Tilt / Rotate         | -                  |           |                    |
| Operating temperature | 0~35°C             |           |                    |
| Average Failure Time  | L70(6k) >36000 (h) |           |                    |

## Accessories

## Photometric

CRI90+



| h(m) | D(m) | E(lx) |
|------|------|-------|
| 75°  |      |       |
| 1.0  | 0.98 | 690   |
| 2.0  | 1.97 | 172   |
| 3.0  | 2.95 | 76    |
| 4.0  | 3.94 | 43    |
| 5.0  | 4.92 | 27    |

## Package

inner box

1.04kg

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.



H:300cm

Distance to the ceiling:200cm

Distance between fixtures:200cm

