




STAR-88



Product specification

INTERIOR RECESSED DOWNLIGHTS



90

Technical Specification

Article number	2218.227F-LEE-19		
LED Consumption	14W		
Fixture Consumption	-		
Current / Voltage	400mA / 33.7Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1541lm	1614lm	1735lm
Delivered Lumen	-	-	-
Beam Angle available	15°/24°/36°/50°		
Driver Technical Specification (Remoted)			
Driver Brand	-	Driver Model	-
Input voltage / Freqency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS III	Optics	PMMA Lens
Protection	IP44	Heat sink	Aluminum die cast
Tilt / Rotate	NONE	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(12k)>66000(h)	Baffle Color available	white / black

Accessories

Photometric

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.