




STARLUX-EYE-2-STLA1



Product specification

INTERIOR COMBO LIGHTS

121
61

Technical Specification

Article number	2314.401-2-ACOT-96		
LED Consumption	7W X2		
Fixture Consumption	-		
Current / Voltage	350mA / 17.8Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen *1	618lm X2	656lm X2	716lm X2
Delivered Lumen	-	-	-
Beam Angle available	15°/24°/36°/50° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trimless	Cold rolled steel
Insulation	CLASS III	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	0~30° / 0~355°	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(11k) >61000(h)	Baffle Color available	white / black


Accessories

ACHO-18
honeycomb louver
+PC sheetSG-002
Striped Glass

Photometric

--	--	--	--	--	--	--	--

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.