



STAR-50-RTW2



Product specification

INTERIOR RECESSED DOWNLIGHTS

98mm

Ø51mm


46

Technical Specification			
Article number	2318.100-ACOT-97		
LED Consumption	10W		
Fixture Consumption	-		
Current / Voltage	250mA / 36.5Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen *1	871lm	913lm	981lm
Delivered Lumen	-	419lm	-
Beam Angle available	Wallwash (Lens)		
Driver Technical Specification (Remoted)			
Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP20	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time		Baffle Color available	white / black

Accessories

Photometric



Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.