




FARFALLA 50-RTF1-1



Product specification

INTERIOR RECESSED DOWNLIGHTS



45

Technical Specification

Article number	2318.203-ACOT-96		
LED Consumption	7W		
Fixture Consumption	-		
Current / Voltage	350mA / 17.8Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	618lm	656lm	716lm
Delivered Lumen	-	538lm	-
Beam Angle available	20°/25°/40°/50° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character

Products Standard	IEC 60598-1
	IEC 62031
Insulation	CLASS II
Protection	IP44
Tilt / Rotate	Non / Non
Operating temperature	0~35°C
Average Failure Time	L70(11k) >61000(h)


Materials

Luminaire	Aluminum die cast
Trim	Aluminum die cast
Optics	PMMA Lens
Heat sink	Forged aluminum
Fixture color available	white / black

Accessories

ACHO-18
honeycomb louver
+PC sheetSG-002
Striped GlassFA50-COLLAR
Collar

Photometric



h(m)	D(m)	E(lx)
25°		
1.0	0.47	2439
2.0	0.94	609
3.0	1.41	271
4.0	1.88	152
5.0	2.36	97

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.