



ASTER-A-64-RSP-J2AM
Product specification

INTERIOR TRACK LIGHTS

Technical Specification

Article number	2319.200-J2AM-350		
LED Consumption	12W		
Fixture Consumption	14W		
Current / Voltage	350mA / 32.9Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1391lm	1454lm	1538lm
Delivered Lumen	-	1342lm	-
Beam Angle available	20°/24°/36°/60°(Lens)		

Driver Technical Specification (Built-in)

Driver Brand	RISE	Driver Model	TDI012NA035EF
Input voltage / Frequency range	120Vac / 50/60Hz	Output Current / Voltage	350mA / 32-38Vdc
Dimming / Flicker	Triac dimming / Free	Certification	ETL
Power Factor	>0.9	Warranty	-

Technical character

Products Standard	UL1574
	-
Insulation	CLASS III
Protection	IP20
Tilt / Rotate	0~90° / 0~355°
Operating temperature	0~35°C
Average Failure Time	L70(10k)>55000(h)


Materials


Luminaire	Aluminum
Trim	-
Optics	PMMA Lens
Heat sink	Forged aluminum
Fixture color available	white / black
Baffle	Aluminum die cast
Baffle Color available	white / black / copper

Accessories

 S-001
snoot

 S-002
Asymmetrical snoot

 SG-001
Striped glass

 H-001
Honeycomb louver

Photometric


h(m)	D(m)	E(lx)
		38°
1.0	0.70	3175
2.0	1.39	793
3.0	2.09	352
4.0	2.78	198
5.0	3.48	127

Remarks


*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.