




## WALLED-EYE-S-LED



## Product specification

## INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	Ø123mm
Dimension	D= Ø134 x H= 108mm



## Technical description

Article number	1018.137		
LED Consumption	12.8W		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen <sup>*1</sup>	1336lm	1387lm	1411lm
Øsystem <sup>*3</sup>	-	-	-
Voltage	36.5V		
Reflector	20°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 12~48 Vdc/350mA,16Watt max.PF 0.90		

## Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	0~30°
Rotate	0~355°
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

## Materials

Luminaire	aluminum die cast
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white / black

## Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

## Photometric

## Accessories

None

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.