



WALLED-EYE-B2-LED

Product specification
INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	R87.5 x 190mm
Dimension	376mm x H= 376mm


Technical description

Article number	1018.149		
LED Consumption	25.5W X2		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	2565lm X 2	2670lm X 2	2712lm X 2
Øsystem ^{*3}	-	-	-
Voltage	36.5V		
Reflector	20°/40°		
CRI	90+		
Driver	Remoted , I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	0~30°
Rotate	0~355°
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white / black

Package

inner box	-	mm 1 kg
outer box	-	mm 0 kg / 0 in 1

Photometric
Accessories

None

Remarks


*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.