




BRANKO-A-110P-STF



Product specification

INTERIOR RECESSED DOWNLIGHTS



 Cut out :
 $3\frac{30}{32}'' \times 3\frac{30}{32}''$

Technical Specification

| | | | |
|----------------|-----------------|--|--|
| Article number | 2418.120-LEA-15 | | |
|----------------|-----------------|--|--|

| | | | |
|-----------------|-----|--|--|
| LED Consumption | 17W | | |
|-----------------|-----|--|--|

| | | | |
|---------------------|-----|--|--|
| Fixture Consumption | 21W | | |
|---------------------|-----|--|--|

| | | | |
|-------------------|---------------|--|--|
| Current / Voltage | 500mA / 34Vdc | | |
|-------------------|---------------|--|--|

| | | | |
|-----|-----|--|--|
| CRI | 90+ | | |
|-----|-----|--|--|

| | | | |
|-----|-------|-------|-------|
| CCT | 2700K | 3000K | 4000K |
|-----|-------|-------|-------|

| | | | |
|--------------|--------|--------|--------|
| LED Lumen *1 | 1917lm | 2004lm | 2120lm |
|--------------|--------|--------|--------|

| | | | |
|-----------------|--------|--------|--------|
| Delivered Lumen | 1424lm | 1489lm | 1575lm |
|-----------------|--------|--------|--------|

| | | | |
|----------------------|------------------------|--|--|
| Beam Angle available | 20°/30°/40°/55° (Lens) | | |
|----------------------|------------------------|--|--|

Driver Technical Specification (Remoted)

| | | | |
|--------------|---------|--------------|-------------|
| Driver Brand | EUCHIPS | Driver Model | PUP20A-1WMC |
|--------------|---------|--------------|-------------|

| | | | |
|--------------------------------|----------------------|--------------------------|-----------------|
| Input voltage / Freqency range | 100-240Vac / 50/60Hz | Output Current / Voltage | 500mA / 9-40Vdc |
|--------------------------------|----------------------|--------------------------|-----------------|

| | | | |
|-------------------|----------------|---------------|----|
| Dimming / Flicker | 0/1-10V / Free | Certification | UL |
|-------------------|----------------|---------------|----|

| | | | |
|--------------|------|----------|---|
| Power Factor | >0.9 | Warranty | - |
|--------------|------|----------|---|

Technical character

Materials

| | | | |
|-------------------|--------|-----------|-------------------|
| Products Standard | UL1598 | Luminaire | Aluminum die cast |
|-------------------|--------|-----------|-------------------|

| | | |
|--|------|-------------------|
| | Trim | Aluminum die cast |
|--|------|-------------------|

| | | | |
|------------|-----------|--------|-----------|
| Insulation | CLASS III | Optics | PMMA Lens |
|------------|-----------|--------|-----------|

| | | | |
|------------|--------------|-----------|-----------------|
| Protection | Wet Location | Heat sink | Forged aluminum |
|------------|--------------|-----------|-----------------|

| | | | |
|---------------|-----------|-------------------------|---------------|
| Tilt / Rotate | Non / Non | Fixture color available | white / black |
|---------------|-----------|-------------------------|---------------|

| | | | |
|-----------------------|--------|--|--|
| Operating temperature | 0~35°C | | |
|-----------------------|--------|--|--|

| | | | |
|----------------------|--------------------|--|--|
| Average Failure Time | L70(10k) >55000(h) | | |
|----------------------|--------------------|--|--|

Accessories

Photometric



H7-1
Honeycomb louver

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.

INSTALLATION OPTIONS



ACCG-22B-PUP20A-1WMC 0/1-10V


ACCG-22B-PUP20D-1WMC DALI

ACCG-22B-PUP20T-1LMC TRIAC

for BRANKO-A-85-2.8"

BRANKO-A-110-3.5" (20-21W)

Type: Gear box




Internal space dimension:
L 8 1/4" (209mm) X W 1 7/8" (48mm) X H 1 5/16" (33mm)



ACCH-12H-100 for BRANKO-A-110-3.5"

Type: New construction plate




ACCH-12B-100-PUP20A-1WMC 0/1-10V

ACCH-12B-100-PUP20D-1WMC DALI

ACCH-12B-100-PUP20T-1LMC TRIAC

for BRANKO-A-110-3.5" (20-21W)

Type: IC Box



ACCI-3

Type: Emergency battery holder


For BillDa emergency led driver-

Model NO. BLD-HM08D-YYY

BLD-HM15D-YYY

BLD-HM20D-YYY

BLD-HM25D-YYY



ACCI-5

Type: Remodel stand

