





WALLED

The extra-thin trim make it smooth to the ceiling just feel like trimless, easy installation perfectly suitable for commercial space.






Article number	1018.141
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	20°/40°
CCT	3000K
CRI	90+


Colours  
Black White



Dimmable



1018.141.0BQS(25.7W)




Article number	1018.137
LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	20°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable







Article number	1018.149
LED Consumption	25.9W X2
Current	700 (mA)
Lumen	2559 (lm) X2
Beam Angle	20°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable





Article number	1018.145
LED Consumption	13W X2
Current	350 (mA)
Lumen	1329 (lm) X2
Beam Angle	20°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable






Article number	1018.139
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	20°/40°
CCT	3000K
CRI	90+


Colours  
Black White



Dimmable



1018.139.0BQS(25.7W)




Article number	1018.135
LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	20°/40°
CCT	3000K
CRI	90+


Colours  
Black White



Dimmable



1018.135.0BQR(12.9W)








Article number	1018.147
LED Consumption	25.9W X2
Current	700 (mA)
Lumen	2559 (lm) X2
Beam Angle	20°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



Article number	1018.143
LED Consumption	13W X2
Current	350 (mA)
Lumen	1329 (lm) X2
Beam Angle	20°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable

