



AGILE

Product specification
INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	Ø168mm
Dimension	D=Ø180 x H=166mm


Technical description

Article number	1618.196		
LED Consumption	51W		
Current	1400mA		
CCT	2700K 3000K 4000K		
Lumen ^{*1}	5185lm 5393lm 5475lm		
Øsystem^{*3}	-		
Voltage	36.4V		
Reflector	20°/40°/60°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 9-42V 1400mA 60w Max		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white/black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric
Accessories

None

Remarks


*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

