


HADES



Product specification

INTERIOR COMBO LIGHT

Installation	Ceiling recessed
Cut out	□ 166 x 319mm
Dimension	D=□ 159 x 312 X H= 117mm

**Technical description**

Article number	1414.419-2		
LED Consumption	25.9W x 2		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	2447lm x 2	2559lm x 2	2636lm x 2
Øsystem ^{*3}	-	-	-
Voltage	37.1V		
Reflector	15°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	0~30°
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
	steel housing
Trimless recessed frame	steel
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**SG-1
reflector+snootHG-1
reflector+
honeycomb louverSGH-1
reflector+
striped glass

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture,
this is the real lumen with the loss because of different design of reflectors and fixtures.

