ARISE

AMIGO-SW-TB1



Product specification

INTERIOR RECESSED DOWN LIGHT			
Installation	Ceiling recessed		
Cut out	□158mm	/m 1	
Dimension	D=⊡170 x H= 152mm	□170 □170	

Technical description				
Article number	1514.405-1			
LED Consumption	25.5W			
Current	700mA			
ССТ	2700K	3000K	4000K	
Lumen *1	2565lm	2670lm	2712lm	
Øsystem ^{*3}	-	-	-	
Voltage	36.5V			
Reflector	20°/40°			
CRI	90+			
Driver	Remoted, I/I	P: 90-264V 50/60)HZ	
Dilvei	O/P: 15-50	V 700mA 35w Ma	ах	

Photometric

Technical character			
Insulation	CLASS III		
Protection	IP 20		
Tilt	0~30°		
Rotate	-		
Operating temperature	-20~40 °C		
Average Failure Time	L70(10k) >60000 (h)		

Materials				
Luminaire	aluminum die cast			
Lummane	steel housing			
Reflector	anodized aluminum			
Heat sink	forged aluminum			
Color available	white / black			

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

