





LED PANEL LIGHT


No glare, No ghosting, Invisible LED dots, Soft, comfortable and attractive ultra thin profile, plus energy saving design of light guide plate, all make it a first priority to appear on commercial space.




Recessed Installation with spring



Recessed Installation




Pendant Installation



Surfaced Mounted




PRODUCT DETAILS




Innovative Plug-and-Play Connector




Flat head screw



18mm width frame to increase illumination area



Multiple paths to dissipate heat




Surfaced Installation






Article number	1660.001
LED Consumption	36W
Voltage	100-240 (V AC)
Lumen	3200 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours White




Article number	1660.002
LED Consumption	36W
Voltage	100-240 (V AC)
Lumen	3200 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours White



Article number	1660.003
LED Consumption	18W
Voltage	100-240 (V AC)
Lumen	1260 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours White



Accessories



PA-01
Hanging Accessories



PA-02
Recessed Accessories



PA-03
Ceiling Accessories

Accessories



PA-01
Hanging Accessories



PA-02
Recessed Accessories



PA-03
Ceiling Accessories

Accessories



PA-01
Hanging Accessories



PA-02
Recessed Accessories



PA-03
Ceiling Accessories