




KUMA

Product specification

INTERIOR RECESSED DOWN LIGHT

| | |
|--------------|--|
| Installation | Wall recessed |
| Cut out | <input type="checkbox"/> 90mm |
| Dimension | D= <input type="checkbox"/> 87 x H= 40mm |

**Technical description**

| | |
|-----------------------|--------------|
| Article number | 1495.203-PIR |
| LED Consumption | 0.5W |
| Current | - |
| CCT | 3000K |
| Lumen ^{*1} | - |
| Øsystem ^{*3} | 5.6lm |
| Voltage | 230Vac |
| Reflector | 120° |
| CRI | 80+ |
| Driver | |

Technical character

| | |
|-----------------------|--------------------|
| Insulation | CLASS I |
| Protection | IP 65 |
| Tilt | - |
| Rotate | - |
| Operating temperature | -20~35 °C |
| Average Failure Time | L70(6k) >36000 (h) |

Materials

| | |
|-----------------|--|
| Luminaire | aluminum and steel bracket tempered glass |
| Reflector | None |
| Heat sink | aluminum dia casting |
| Color available | white / black / brown |
| | |

Package

| | |
|-----------|------------------|
| inner box | mm 1 kg |
| outer box | mm 0 kg / 0 in 1 |

Photometric**Accessories****Remarks**

B6 Type of switch box



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

