




## TRUNKING-L



## Product specification

**INTERIOR PENDENT LIGHT**

Installation	PENDENT LIGHT
Cut out	
Dimension	L=1437mm W=67mm H=54mm

**Technical description**

Article number	1610.015A
LED Consumption	48W
Current	-
Lumen <sup>*1</sup>	5000lm
Øsystem <sup>*3</sup>	-
Voltage	100-240Vac
Beam Angle	30° / 60° / 90° / Double 20°
CCT	3000K
CRI	80+
Driver	Built-in, I/P : 100-240Vac 50/60 HZ O/P : 1200mA

**Technical character**

Insulation	CLASS I
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

**Materials**

Luminaire	aluminum extruded body and plastic end caps
Diffuser	
Reflector	Lens
Heat sink	aluminum extruded
Color available	paint white

**Package**

inner box	mm
outer box	mm

**Photometric****Accessories**

None

**Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.