


TRUNKING-L



Product specification

INTERIOR PENDENT LIGHT

| | |
|--------------|------------------------|
| Installation | PENDENT LIGHT |
| Cut out | |
| Dimension | L=1437mm W=67mm H=54mm |

**Technical description**

| | |
|-----------------------|---|
| Article number | 1610.016A |
| LED Consumption | 72W |
| Current | - |
| Lumen ^{*1} | 7400lm |
| Øsystem ^{*3} | - |
| Voltage | 100-240Vac |
| Beam Angle | 30° / 60° / 90° / Double 20° |
| CCT | 3000K |
| CRI | 80+ |
| Driver | Built-in, I/P : 100-240Vac 50/60 HZ O/P : 1800mA |

Technical character

| | |
|-----------------------|--------------------|
| Insulation | CLASS I |
| Protection | IP 20 |
| Tilt | - |
| Rotate | - |
| Operating temperature | -20~40 °C |
| Average Failure Time | L70(6k) >36000 (h) |

Materials

| | |
|-----------------|--|
| Luminaire | aluminum extruded body and plastic end cap |
| | Diffuser |
| Reflector | Lens |
| Heat sink | aluminum extruded |
| Color available | paint white |

Package

| | |
|-----------|----|
| inner box | mm |
| outer box | mm |

Accessories

None

Remarks**Photometric**

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.