



SNOOT

Material: Steel trim with powder coating finish, Alu. extrusion housing & heatsink, Alu. forging heatsink, plastic baffle with liquid coating finish. Housing & trim can be made into black or white finish.

Application: Residential, shopping mall, shops, office, restaurant & bar, museum, art gallery, showroom, exhibition center





Striped Glass

or



Honeycomb Louver

or



Diffusion Sheet



Fixed

or



Long Snoot

or



Short Snoot

Light engine



Fixed



Short snoot
(adjustable)



Long snoot
(adjustable)



Wall washer



Spotlight



Pendant




1X1, 1X2, 1X3 trims are available, adjustable, downlight, wall washer, pendant, spot modeules can be installed tool-free. Combination of different lighting modules can be used in a single area for different lighting purposes. Snoot baffle design can reduce the presence of the fixture.

Trim





SNOOT-T1



Colours  
Black White




SNOOT-T2



Colours  
Black White



SNOOT-T3





Colours  
Black White

Trimless





SNOOT-TL1



Colours  
Black White




SNOOT-TL2



Colours  
Black White



SNOOT-TL3



Colours  
Black White




Article number	1800.003
LED Consumption	12.8W
Current	350 (mA)
Lumen	1387 (lm)
Beam Angle	15°/24°/38°/60°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



h (m)	D (m)	E (lx)
42.5°		
0.5	0.38	5951
1.0	0.76	1488
1.5	1.14	661
2.0	1.52	371
2.5	1.90	238

Accessories



SG7-1
striped glass



H7-1
honeycomb louver



DS7-1
diffusion sheet





Article number	1800.004
LED Consumption	12.8W
Current	350 (mA)
Lumen	1387 (lm)
Beam Angle	15°/24°/38°/60°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable







Article number	1800.005
LED Consumption	12.8W
Current	350 (mA)
Lumen	1387 (lm)
Beam Angle	15°/24°/38°/60°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



h(m)	D(m)	E(lx)
	41.1°	
0.5	0.37	3582
1.0	0.74	895
1.5	1.11	398
2.0	1.49	223
2.5	1.86	143

Accessories



SG7-1
striped glass



H7-1
honeycomb louver



DS7-1
diffusion sheet





Article number	1800.006
LED Consumption	12.8W
Current	350 (mA)
Lumen	1387 (lm)
Beam Angle	15°/24°/38°/60°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



h(m)	D(m)	E(lx)
	38°	
0.5	0.34	5154
1.0	0.68	1288
1.5	1.02	572
2.0	1.37	322
2.5	1.71	206

Accessories



SG7-1
striped glass



H7-1
honeycomb louver



DS7-1
diffusion sheet




Article number	1800.002
LED Consumption	6.4W
Voltage	48 (Vac)
Lumen	626 (lm)
Beam Angle	10°/20°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable





Article number	1800.001
LED Consumption	6.4W
Current	350 (mA)
Lumen	542 (lm)
Beam Angle	10°/20°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



h(m)	D(m)	E(lx)
20.6°		
0.5	0.18	6336
1.0	0.36	1584
1.5	0.54	704
2.0	0.72	396
2.5	0.90	253