



SLIMDUET (AM) system


SLIMDUET (AM)

Ultimate slim, perfect style


Innovative slim linear connecting system, a perfect combination between tracks and LED fixtures. Not only emphasizing on characteristics and rapid installation of the modules, also creates simple and clean appearance. Unique designed spot, panel and downlight modules are available for multitasking lighting requirement to the area. This is a perfect solution to maximize lighting creativity.

SLIMDUET^(AM)


SLIMDUET TRACK



SDT Surface mounted & Pendant track P.15



SDR Trimless recessed track P.15



SDF Trim recessed track P.15

SLIMDUET MODULES

		Series name	LED Consumption	Lumen	P.23
		SLIMDUET-K	11W 22W 33W	1000 (lm) 2000 (lm) 3000 (lm)	
		SLIMDUET-P	9.2W 18.4W 27.5W	472(lm) 1197(lm) 1428(lm)	P.25
		SLIMDUET-W	11W	462 (lm)	P.27
		SLIMDUET-S	6.4W 12.7W	626 (lm) 1114 (lm)	P.29
		SLIMDUET-GR	5.3W	100 (lm)	P.31
		SLIMDUET-GL	5.3W	399 (lm)	P.33
		SLIMDUET-C	6.4W	626 (lm)	P.35
		SLIMDUET-KC	22W	2000 (lm)	P.37
		SLIMDUET-KS	11W	1000 (lm)	P.39






SLIMDUET (AM)


Slim linear connecting system, can be recessed, surface mounted or pendant. Suitable for all kinds of interior environment.

The LED modules are designed with simple linear style, each series perform its own function, making lighting design easier than ever.

SLIMDUET^(AM)







SLIMDUET (AM)



LED fixture installation is designed to be simple and convenient, just plug and play, tools-free, significant savings on installation and maintenance. The track cover can be moved or cut to fit with the LED fixture to make overall appearance succinct.

Track section



Product performance


Article number	L
SDT-10-36	35.98"(914mm)
SDT-10-72	71.97"(1828mm)
SDT-10-96	95.98"(2438mm)

Article number	L
SDR-10-36	35.98"(914mm)
SDR-10-72	71.97"(1828mm)
SDR-10-96	95.98"(2438mm)


Article number	L
SDF-15-36	35.98"(914mm)
SDF-15-72	71.97"(1828mm)
SDF-15-96	95.98"(2438mm)

Colours  Black  White


Accessories




Article number: SDR-04
Type : Trimless recessed
vertical corner




Article number: SDF-04
Type : Trim recessed
vertical corner



Article number : SDR-05
Type : Trimless recessed
horizontal corner




Article number : SDT-05
Type : Surface mounted &
pendant horizontal corner



Article number : SDF-12
Type : Trim recessed
horizontal corner



SLIMDUET (AM)

INSTALLATION GUIDE




APPLICATION –
connecting power in different conditions for continuous connection



1 Single Power, Single Track




Using power end cap (SDC-03) as power feed





2 Single Power, Multiple Tracks




Using circuit joint (SDC-01D) to connect between tracks



3 Multiple Powers, Multiple Tracks




Using power joint (SDC-02D) to connect more drivers




Do not install fixture between the tracks
when a new driver is connected into the circuit

ACCESSORIES


Connections




Article number : SDC-01D
Type : Circuit joint




Article number : SDC-02D
Type : Power joint
Length : 78.74" (200cm)




Article number : SDC-07D
Type : New circuit joint




Article number : SDC-03
Type : Surface mounted & pendant & trimless
recessed end cap with power cord
Length : 78.74" (200cm)




Article number : SDC-03A
Type : Trim recessed end cap
with power cord
Length : 78.74" (200cm)




Article number : SDC-04
Type : Surface mounted & pendant & trimless
recessed end cap without power cord




Article number : SDC-04A
Type : Trim recessed end cap
without power cord




Article number : SDC-05
Type : Surface mounted joint



Article number : SDC-05A
Type : recessed reinforced joint




Article number : SDC-06
Type : Surface mounted & Pendant
reinforced plate



Article number : SDI-10
Type : Trim recessed clip

Pendant




Article number : SDI-05
Type : Pendant kit for power connection
without power cord
Length : 59.06" (150cm)



Article number : SDI-06
Type : Pendant kit without
power cord
Length : 59.06" (150cm)

SLIMDUET (AM)

Application Illustration




NOTE:

1. Max wattage linkable per loop for 24VDC is 96W.
2. Max length of track linkable per loop is 393.7\"(10M), and the max cable length between driver and track is 78.74\"(2M).
3. Dimming modules are compatible to PWM dimming driver only.
4. To use drivers not on recommended list, it require compatibility test before installation.
5. Use only with class 2 power unit

Tracks allows continuous linkable without limitation, also can divide into sections to light up individual area, making lighting application easy as 123.

Driver Installation



Driver needs to hide into the ceiling









SLIMDUET (AM)





SLIMDUET-K



Colours  
Black White

Baffle :   
Black White Piano black

Product performance

SLIMDUET-K5

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1817.406A-AM-V	11W	24V DC	1000 (lm)	15°/30°/40°	30/90+	Push

SLIMDUET-K10

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1817.406B-AM-V	22W	24V DC	2000 (lm)	15°/30°/40°	30/90+	Push



SLIMDUET-K15

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1817.406C-AM-V	33W	24V DC	3000 (lm)	15°/30°/40°	30/90+	Push





SLIMDUET-P Seamless Installation








Product performance

Article number	L
SDE-01	157.48" (4000mm)
SDE-02	590.55" (15000mm)

Colours 
White

SLIMDUET-P



Colours  Black  White


Product performance

SLIMDUET-P3						
Article number	LED Consumption	Voltage	System Lumen	Beam Angle	CCT/CRI	Locking Type
1817.410A-AM-V	9.2W	24V DC	472 (lm)	115°	30/80+	Twist
SLIMDUET-P6						
Article number	LED Consumption	Voltage	System Lumen	Beam Angle	CCT/CRI	Locking Type
1817.410B-AM-V	18.4W	24V DC	1197 (lm)	115°	30/80+	Twist
SLIMDUET-P9						
Article number	LED Consumption	Voltage	System Lumen	Beam Angle	CCT/CRI	Locking Type
1817.410C-AM-V	27.5W	24V DC	1428 (lm)	115°	30/80+	Twist






SLIMDUET-W



1817.407A-AM-V



- Colours ☒ Black ☐ White
- Baffle : ☒ Black


Product performance

Article number	LED Consumption	Voltage	System Lumen	Beam Angle	CCT/CRI	Locking Type
1817.407A-AM-V	11W	24V DC	462 (lm)	wallwash	30/90+	Push







SLIMDUET-S



1617.407-AM-V



1617.411-AM-V



- Colours
- Black White
- Baffle :
- Black White Copper

Product performance

SLIMDUET-S1

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1617.407-AM-V	6.4W	24V DC	626 (lm)	15°/20°	30/90+	Twist


SLIMDUET-S2

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1617.411-AM-V	12.7W	24V DC	1114 (lm)	16°/21°/35°	30/90+	Twist






SLIMDUET-GR



1817.401-AM-V



Colours  
Black White


Product performance

Article number	LED Consumption	Voltage	System Lumen	Beam Angle	CCT/CRI	Locking Type
1817.401-AM-V	5.3W	24V DC	214 (lm)	90°	30/90+	Twist






SLIMDUET-GL



1617.409A-AM-V



- Colours
- Black
 - White
- Baffle :
- Black
 - White
 - Piano black


Product performance

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1617.409A-AM-V	5.3W	24V DC	399 (lm)	19°/35°	30/90+	Twist






SLIMDUET-C



1617.410-AM-V



- Colours ● Black ○ White
- Baffle : ● Black ○ White ● Copper


Product performance

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1617.410-AM-V	6.4W	24V DC	626 (lm)	10°/ 20°	30/90+	Twist






SLIMDUET-KC



1817.411-AM-V



- Colours: ☒ Black ☐ White
- Baffle: ☒ Black ☐ White ☐ Piano black



Product performance

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1817.411-AM-V	22W	24V DC	2000 (lm)	15°/25°/40°	30/90+	Twist






SLIMDUET-KS



1817.413-AM-V



- Colours ☒ Black ☐ White
- Baffle : ☒ Black ☐ White ☐ Piano black

Article number	LED Consumption	Voltage	Lumen	Beam Angle	CCT/CRI	Locking Type
1817.413-AM-V	11W	24V DC	1000 (lm)	15°/30°/40°	30/90+	Twist

