



Color available - A / B / C / D

● Black ○ White
 Black White


DEINO




Using the heatsink as housing brings out better overall appearance to the fixture.
Track spot, surface mount, pull down recess is also available.



Article number	1618.234
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+



Dimmable



Accessories




SG8-2
striped glass



H12-2
honeycomb louver




DS7-2
diffusion sheet




B11-2
barndoor



Article number	1618.157
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+



Dimmable



Accessories




SG8-2
striped glass



H12-2
honeycomb louver



DS7-2
diffusion sheet





B11-2
barndoor




Article number	1618.233
LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+



Dimmable




Accessories




SG8-1 striped glass H12-1 honeycomb louver DS7-1 diffusion sheet B11-1 barndoor



Article number	1618.156
LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+



Dimmable



Accessories



SG8-1 striped glass H12-1 honeycomb louver DS7-1 diffusion sheet B11-1 barndoor




Article number 1619.210

LED Consumption	39.8W
Current	1050 (mA)
Lumen	3888 (lm)
Beam Angle	10°/24°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable




Article number 1619.209

LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable




Article number 1619.208

LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



Accessories




SG8-2
striped glass



H12-2
honeycomb louver



DS7-2
diffusion sheet



B11-2
barndoor

Accessories



SG8-1
striped glass



H12-1
honeycomb louver



DS7-1
diffusion sheet



B11-1
barndoor




Article number 1619.305

LED Consumption	39.8W
Current	1050 (mA)
Lumen	3888 (lm)
Beam Angle	10°/24°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable




Article number 1619.304

LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable




Article number 1619.303

LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



Accessories




SG8-2
striped glass



H12-2
honeycomb louver



DS7-2
diffusion sheet



B11-2
barndoor

Accessories




SG8-1
striped glass



H12-1
honeycomb louver



DS7-1
diffusion sheet



B11-1
barndoor




Article number	1619.201
LED Consumption	39.8W
Current	1050 (mA)
Lumen	3888 (lm)
Beam Angle	10°/24°/40°
CCT	3000K
CRI	90+

Colours  
Black White




Dimmable




Article number	1719.202
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable



Accessories




SG8-2
striped glass



H12-2
honeycomb louver



DS7-2
diffusion sheet



B11-2
barndoor



DEINO COMBO LIGHTS


Allowing 0~86 degree tilt angle with pull out mechanism
 Design with baffle to make the fixture more concise.
 Equipped with Z shape ceiling clip, making installation easier.
 Using the heatsink as housing brings out better overall appearance to the fixture.








Article number	1614.412
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White




Dimmable





Article number	1614.417
LED Consumption	25.9WX2
Current	700 (mA)
Lumen	2559 (lm)X2
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White




Dimmable






Article number	1614.419
LED Consumption	25.9WX3
Current	700 (mA)
Lumen	2559 (lm)X3
Beam Angle	18°/26°/38°/55°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable








Article number	1614.410
LED Consumption	13W
Current	350 (mA)
Lumen	1329 (lm)
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable






Article number	1614.413
LED Consumption	13WX2
Current	350 (mA)
Lumen	1329 (lm)X2
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+

Colours  
Black White




Dimmable



Article number	1614.415
LED Consumption	13WX3
Current	350 (mA)
Lumen	1329 (lm)X3
Beam Angle	13°/26°/38°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable

