



LED PANEL LIGHT


No glare, no ghosting, invisible LED dots, soft, comfortable and attractive ultra thin profile, plus energy saving design of light guide plate, all make it a first priority to appear on commercial space.




Recessed installation with spring



Recessed installation



Pendant installation



Surfaced mounted




Product details




Innovative Plug-and-Play Connector




Flat head screw



18mm width frame to increase illumination area



Multiple paths to dissipate heat





Surfaced Installation






Article number	1660.001
LED Consumption	36W
Voltage	100-240 (Vac)
Lumen	3200 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours  White




Article number	1660.002
LED Consumption	36W
Voltage	100-240 (Vac)
Lumen	3200 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours  White



Article number	1660.003
LED Consumption	18W
Voltage	100-240 (Vac)
Lumen	1260 (lm)
Beam Angle	110°
CCT	3000K
CRI	80+

Colours  White



Accessories



PA-01
Hanging accessories



PA-02
Recessed accessories



PA-03
Ceiling accessories

Accessories



PA-01
Hanging accessories



PA-02
Recessed accessories



PA-03
Ceiling accessories

Accessories



PA-01
Hanging accessories



PA-02
Recessed accessories



PA-03
Ceiling accessories