


STAR SERIES (AM-C.C.)



STAR (AM)

Small enough to be held by 2 fingers easily. Which is small and compact for blending into the ceiling perfectly, High Lumen and did not even notice the small lighting fixture in the ceiling. With a unique anti-glare feature to present soft and comfortable light emission providing UGR<19. It can apply to numerous situations, such as residential and commercial lighting.

Shape
(Baffle Size)




Round 1.5" Square 1.5" 2 lamp 1.5"

Mountings



Recessed Trim Recessed Trimless

Light distributions



Fixed Adjustable Wallwash

STAR-1.5"

recessed downlights



LEA-09B



LEA-09B-HE



LEA-09B-DW
Dim to warm



LEA-28-HE
(ETL pending)

Only applicable to single-light modules



Fixed



Adjustable



Wallwash

Round

Trim



Trimless



Square

Trim



Trimless



Multiple lights

2 Lamp
Trim





STAR-1.5"

RISE's STAR-1.5" deliver high lumens to your spaces while remaining fully workable from below the ceiling plane.

FEATURES


- STAR-1.5" downlight offer a tiny new form element for a minutest downlight artistic.
- Micro trim style is well suited with sheetrock, ACT, wood/ millwork, and many other ceiling materials
- Industry leading luminescence and craftsmanship

STAR-1.5"

Light Engine

We design heat sinks of different heights.

When encountering low ceilings or obstructions in the ceiling space, you can switch to different height light engine heat sinks to save space, allowing the entire space to maintain consistent lighting fixtures to meet illumination needs.




Cut-off angle

Visual Comfort with Low Glare

Designed with a 36° cut-off angle, the fixture effectively blocks excess light and prevents direct glare into the eyes.


It delivers focused yet soft illumination, making it ideal for environments where visual comfort is essential—such as retail displays, reception areas, and high-end residential spaces.




Bigger the cut-off angle, the more the visible glare is reduced




Doubles combinations




Fixed



Adjustable




Wallwash



Constant current

1 to multiple fixtures

Rise's STAR-1.5" are compatible with all common lighting controls; choose from Traic, 0-10V dimming.



Remote driver


Using a driver to drive up multiple fixtures at a time for more economical solution.

Driver Storage

***Recommended Installation* :**
Drivers can be stored into maintenance hole of the enclosure for easy access.

Size : 20" x 16" x H:3.94"

Max circuit length 1181¹/₈"(30M) with wire gauge 12AWG.



Optional driver available



KIG-040-DW

Type: Driver

Triac / 0-10V/1-10V/Potentiometer/10V
PWM 5 in 1 Dimmable LED driver
Multi-current output series 40W
For 2~3T



PUP10A-1WMC-700

Type: Driver

0/1-10V
Output: 500mA/2-20V/10W
400mA/2-21V/8.4W
For 1T



PUP20A-1WMC

Type: Driver

0/1-10V
Output: 500mA/9-40V/20W
400mA/9-45V/18W
For 1~2T



PUP10T-1LMC-700

Type: Driver

Triac
Output: 500mA/2-20VDC/10W
400mA/2-21VDC/8.4W
For 1T



PUP20T-1LMC

Type: Driver

Triac
Output: 500mA/9-40V/20W
400mA/9-45V/18W
For 1~2T



PUP10D-1WMC-700

Type: Driver

Dali
Output: 500mA/2-20V/10W
400mA/2-21V/8.4W
For 1T



PUP20D-1WMC

Type: Driver


Dali
Output: 500mA/9-40V/20W
400mA/9-45V/18W
For 1~2T




ACOT-106

Type: Quick connector

NON-IC



IC-BOX



STAR-1.5" round / square
fixed / adjustable / wallwash




Specification

2700 K, 3000 K, 4000 K,
CRI ≥ 90

TRIAC, 1-10V

Types (round & square)



Colours

Bezel :  Black  White

Baffle :  Black  White


Wallwash baffle :  Black

Beam Angle

   
20°/25°/35°/50° (Lens)



Wallwash (Lens)





STAR-50-RTF



Article number	2118.564-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	703 (lm)
HE Delivered Lumen*	888 (lm)
Beam Angle	20°/30°/40°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2118.564-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	464 (lm)
Beam Angle	25°/30°/40°/45° (Lens)
CCT	1800K-3000K
CRI	90+

**Dimmable**

TRIAC	1-10V
-------	-------




⌀ Cut out : 1 25/32" (45mm)


STAR-50-RTA



Article number	2118.565-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	654 (lm)
HE Delivered Lumen*	842 (lm)
Beam Angle	20°/30°/40°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2118.565-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	406 (lm)
Beam Angle	20°/25°/35°/40° (Lens)
CCT	1800K-3000K
CRI	90+

**Dimmable**

TRIAC	1-10V
-------	-------




⌀ Cut out : 1 25/32" (45mm)

STAR-50-RTW




Article number	2318.100-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	398 (lm)
HE Delivered Lumen*	544 (lm)
Beam Angle	Wallwash (Lens)
CCT	3000K
CRI	90+
Article number	2318.100-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	273 (lm)
Beam Angle	Wallwash (Lens)
CCT	1800K-3000K
CRI	90+

*Wallwash lens — best optical matching angle: 15°

**Dimmable**

TRIAC	1-10V
-------	-------



⌀ Cut out : 1 25/32" (45mm)

Accessories

ACHO-18
honeycomb louver
+PC sheet




SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures

STAR-50-RTLFL




Article number	2118.659F-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	703 (lm)
HE Delivered Lumen*	888 (lm)
Beam Angle	20°/30°/40°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2118.659F-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	464 (lm)
Beam Angle	25°/30°/40°/45° (Lens)
CCT	1800K-3000K
CRI	90+



Dimmable

TRIAC	1-10V
-------	-------




⌀ Cut out : 2 4/32" (54mm)

STAR-50-RTLA




Article number	2118.660F-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	654 (lm)
HE Delivered Lumen*	842 (lm)
Beam Angle	20°/30°/40°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2118.660F-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	406 (lm)
Beam Angle	20°/25°/35°/40° (Lens)
CCT	1800K-3000K
CRI	90+



Dimmable

TRIAC	1-10V
-------	-------




⌀ Cut out : 2 4/32" (54mm)

STAR-50-RTLW




Article number	2318.200F-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	398 (lm)
HE Delivered Lumen*	544 (lm)
Beam Angle	Wallwash (Lens)
CCT	3000K
CRI	90+
Article number	2318.200F-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	273 (lm)
Beam Angle	Wallwash (Lens)
CCT	1800K-3000K
CRI	90+

*Wallwash lens — best optical matching angle: 15°



Dimmable

TRIAC	1-10V
-------	-------



⌀ Cut out : 2 4/32" (54mm)

Accessories



ACHO-18
honeycomb louver
+PC sheet



SG-002
Striped Glass



ACOT-107
Suction cup

Accessories are not suitable for wallwash fixtures


STAR-50-STF


Article number 2218.117-LEA-09B


Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	676 (lm)
HE Delivered Lumen*	877 (lm)
Beam Angle	20°/25°/35°/50° (Lens)
CCT	3000K
CRI	90+

Article number 2218.117-LEA-09B-DW

Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	438 (lm)
Beam Angle	20°/30°/40°/45° (Lens)
CCT	1800K-3000K
CRI	90+


Dimmable

TRIAC	1-10V
-------	-------



△ Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)


STAR-50-STA


Article number 2218.118-LEA-09B


Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	632 (lm)
HE Delivered Lumen*	780 (lm)
Beam Angle	20°/25°/35°/50° (Lens)
CCT	3000K
CRI	90+

Article number 2218.118-LEA-09B-DW

Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	355 (lm)
Beam Angle	20°/30°/35°/40° (Lens)
CCT	1800K-3000K
CRI	90+


Dimmable

TRIAC	1-10V
-------	-------



△ Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)

STAR-50-STW



Article number 2318.104-LEA-09B

Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	398 (lm)
HE Delivered Lumen*	535 (lm)
Beam Angle	Wallwash (Lens)
CCT	3000K
CRI	90+


Article number 2318.104-LEA-09B-DW

Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	277 (lm)
Beam Angle	Wallwash (Lens)
CCT	1800K-3000K
CRI	90+

*Wallwash lens — best optical matching angle: 15°


Dimmable

TRIAC	1-10V
-------	-------



△ Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)

Accessories



ACHO-18
honeycomb louver
+PC sheet




SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures

STAR-50-STLF





Article number	2218.208A-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	676 (lm)
HE Delivered Lumen*	877 (lm)
Beam Angle	20°/25°/35°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2218.208A-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	438 (lm)
Beam Angle	20°/30°/40°/45° (Lens)
CCT	1800K-3000K
CRI	90+




Dimmable

TRIAC	1-10V
-------	-------




Cut out : 1³¹/₃₂"X1³¹/₃₂" (50X50mm)

STAR-50-STLA





Article number	2218.209A-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	632 (lm)
HE Delivered Lumen*	780 (lm)
Beam Angle	20°/25°/35°/50° (Lens)
CCT	3000K
CRI	90+
Article number	2218.209A-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	355 (lm)
Beam Angle	20°/30°/35°/40° (Lens)
CCT	1800K-3000K
CRI	90+



Dimmable

TRIAC	1-10V
-------	-------




Cut out : 1³¹/₃₂"X1³¹/₃₂" (50X50mm)

STAR-50-STLW




Article number	2318.204A-LEA-09B
Fixture Consumption	10W
Current	500 (mA)
Delivered Lumen	398 (lm)
HE Delivered Lumen*	535 (lm)
Beam Angle	Wallwash (Lens)
CCT	3000K
CRI	90+
Article number	2318.204A-LEA-09B-DW
Fixture Consumption	11W
Current	500 (mA)
Delivered Lumen	277 (lm)
Beam Angle	Wallwash (Lens)
CCT	1800K-3000K
CRI	90+

*Wallwash lens — best optical matching angle: 15°



Dimmable

TRIAC	1-10V
-------	-------



Cut out : 1³¹/₃₂"X1³¹/₃₂" (50X50mm)

Accessories



ACHO-18
honeycomb louver
+PC sheet



SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures



STAR-50-RTF2

**Article number 2118.564-LEA-28-HE**

	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	

**Dimmable**

TRIAC	1-10V
-------	-------



⊗ Cut out : 1²⁵/₃₂" (45mm)



STAR-50-RTA2

**Article number 2118.565-LEA-28-HE**

	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	

**Dimmable**

TRIAC	1-10V
-------	-------




⊗ Cut out : 1²⁵/₃₂" (45mm)

STAR-50-RTW2

**Article number 2318.100-LEA-28-HE**

	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	Wallwash (Lens)	
CCT	3000K	
CRI	90+	



*Wallwash lens — best optical matching angle: 15°



ETL pending

Dimmable

TRIAC	1-10V
-------	-------



⊗ Cut out : 1²⁵/₃₂" (45mm)

Accessories

ACHO-18
honeycomb louver
+PC sheet




SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures

STAR-50-RTL2




Article number	2118.659F-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (mA)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------




⌀ Cut out : 2 4/32" (54mm)

STAR-50-RTLA2




Article number	2118.660F-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------




⌀ Cut out : 2 4/32" (54mm)

STAR-50-RTLW2




Article number	2318.200F-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	Wallwash (Lens)	
CCT	3000K	
CRI	90+	

*Wallwash lens — best optical matching angle: 15°



Dimmable

TRIAC	1-10V
-------	-------



⌀ Cut out : 2 4/32" (54mm)

Accessories are not suitable for wallwash fixtures

Accessories



ACHO-18
honeycomb louver
+PC sheet


SG-002
Striped Glass

ACOT-107
Suction cup


STAR-50-STF2



Article number	2218.117-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	

**Dimmable**

TRIAC	1-10V
-------	-------




Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)


STAR-50-STA2



Article number	2218.118-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	

**Dimmable**

TRIAC	1-10V
-------	-------




Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)

STAR-50-STW2




Article number	2318.104-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	Wallwash (Lens)	
CCT	3000K	
CRI	90+	

*Wallwash lens — best optical matching angle: 15°

**Dimmable**

TRIAC	1-10V
-------	-------



Cut out : 1²⁶/₃₂"X1²⁶/₃₂" (46X46mm)

Accessories

ACHO-18
honeycomb louver
+PC sheet




SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures

STAR-50-STLF2




Article number	2218.208A-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------




Cut out : 1 31/32"X1 31/32" (50X50mm)

STAR-50-STLA2




Article number	2218.209A-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------




Cut out : 1 31/32"X1 31/32" (50X50mm)

STAR-50-STLW2




Article number	2318.204A-LEA-28-HE	
	NON-IC	IC
LED Consumption	10.4W	8.5W
Current	600 (mA)	500 (mA)
Lumen	1312 (lm)	1114 (lm)
Beam Angle	Wallwash (Lens)	
CCT	3000K	
CRI	90+	

*Wallwash lens — best optical matching angle: 15°



Dimmable

TRIAC	1-10V
-------	-------



Cut out : 1 31/32"X1 31/32" (50X50mm)

Accessories



ACHO-18
honeycomb louver
+PC sheet




SG-002
Striped Glass

Accessories are not suitable for wallwash fixtures

STAR-1.5" Multiple lights

fixed / adjustable / wallwash




Specification

2700 K, 3000 K, 4000 K,
CRI ≥ 90

TRIAC, 1-10V

Types



Colours

Bezel :  Black  White

Baffle :  Black  White



Wallwash baffle :  Black

Beam Angle



20°/25°/35°/50° (Lens)




Wallwash (Lens)



STAR-50-2-STF




Article number	2214.413-2-LEA-09B	
	NON-IC	IC
Fixture Consumption	20W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	1441 (lm)	1206 (lm)
HE Delivered Lumen*	888 (lm)X2	-
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	
Article number	2214.413-2-LEA-09B-DW	
	NON-IC	IC
Fixture Consumption	22W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	464 (lm)X2	-
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	1800K-3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------



Cut out : 2¹³/₃₂"x4²⁴/₃₂" (61x121mm)


Accessories



STAR-50-2-STA




Article number	2214.410-2-LEA-09B	
	NON-IC	IC
Fixture Consumption	20W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	1369 (lm)	1137 (lm)
HE Delivered Lumen*	842 (lm)X2	-
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	3000K	
CRI	90+	
Article number	2214.410-2-LEA-09B-DW	
	NON-IC	IC
Fixture Consumption	22W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	406 (lm)X2	-
Beam Angle	20°/30°/40°/50° (Lens)	
CCT	1800K-3000K	
CRI	90+	



Dimmable

TRIAC	1-10V
-------	-------




Cut out : 2¹³/₃₂"x4²⁴/₃₂" (61x121mm)

STAR-50-2-STW




Article number	2314.402-2-LEA-09B	
	NON-IC	IC
Fixture Consumption	20W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	398 (lm)X2	-
HE Delivered Lumen*	544 (lm)X2	-
Beam Angle	Wallwash (Lens)	
CCT	3000K	
CRI	90+	
Article number	2314.402-2-LEA-09B-DW	
	NON-IC	IC
Fixture Consumption	22W	-
Current	500 (mA)	400 (mA)
Delivered Lumen	273 (lm)X2	-
Beam Angle	Wallwash (Lens)	
CCT	1800K-3000K	
CRI	90+	

*Wallwash lens — best optical matching angle: 15°



Dimmable

TRIAC	1-10V
-------	-------



Cut out : 2¹³/₃₂"x4²⁴/₃₂" (61x121mm)

Accessories are not suitable for wallwash fixtures




INSTALLATION OPTIONS



KIG-040-DWJ

Triac/Phase , 0-10V , 1-10V , Potentiometer ,
10V PWM 5 in 1 dimming
40W 2-3T
Type: Gear box





ACCH-13-R45-S46

for STAR50 round / square trim
Type: New construction plate

Cut out:

Round : Ø1²⁶/₃₂" (Ø46mm)

Square : □1²⁶/₃₂" (□46mm)




ACCH-13-R54-S50

for STAR50 round / square trimless
Type: New construction plate

Cut out:

Round : Ø2⁴/₃₂" (Ø54mm)

Square : □1³¹/₃₂" (□50mm)






ACCH-12-61X181

for STAR50 Multiple

Type: New construction plate

Cut out:

2 T/TL : $2\frac{13}{32}$ "x $4\frac{24}{32}$ " (61x121mm)



* Cutout accessories are available for different cutout dimensions




ACCH-12G-61X181

for STAR50 Multiple both trim & trimless

Type: IC Box


Cut out:

2 T/TL : $2\frac{13}{32}$ "x $4\frac{24}{32}$ " (61x121mm)



* Cutout accessories are available for different cutout dimensions

Cutout accessories



ACCI-10-R45-S46

for STAR50 Trim

Cut out:

Round : $\varnothing 1\frac{26}{32}$ " ($\varnothing 46$ mm)

Square : $\square 1\frac{26}{32}$ " ($\square 46$ mm)



ACCI-10-R54-S50

for STAR50 Trimless

Cut out:

Round : $\varnothing 2\frac{4}{32}$ " ($\varnothing 54$ mm)

Square : $\square 1\frac{31}{32}$ " ($\square 50$ mm)



ACCI-10A-R45-S46

for STAR50 Double Trim

Cut out:

Round : $\varnothing 1\frac{26}{32}$ " ($\varnothing 46$ mm)

Square : $\square 1\frac{26}{32}$ " ($\square 46$ mm)



ACCI-10A-R54-S50

for STAR50 Double Trimless

Cut out:



Round : $\varnothing 2\frac{4}{32}$ " ($\varnothing 54$ mm)

Square : $\square 1\frac{31}{32}$ " ($\square 50$ mm)



20°

Fixed UGR<16



 2118.564-LEA-09B
 2118.659F-LEA-09B


H(m)	D(m)	E(lx)
20°		
1.0	0.38	2534
2.0	0.76	633
3.0	1.14	281
4.0	1.52	158
5.0	1.91	101



30°

Fixed UGR<13



 2118.564-LEA-09B
 2118.659F-LEA-09B


H(m)	D(m)	E(lx)
30°		
1.0	0.49	2066
2.0	0.98	516
3.0	1.47	229
4.0	1.95	129
5.0	2.44	82



40°

Fixed UGR<19



 2118.564-LEA-09B
 2118.659F-LEA-09B


H(m)	D(m)	E(lx)
40°		
1.0	0.70	1044
2.0	1.40	261
3.0	2.10	116
4.0	2.80	65
5.0	3.50	41



50°

Fixed UGR<22



 2118.564-LEA-09B
 2118.659F-LEA-09B


H(m)	D(m)	E(lx)
50°		
1.0	0.99	639
2.0	1.97	159
3.0	2.96	71
4.0	3.95	39
5.0	4.93	25



20°

Fixed UGR<19



 2118.564-LEA-09B-HE
 2118.659F-LEA-09B-HE


H(m)	D(m)	E(lx)
20°		
1.0	0.39	2794
2.0	0.79	698
3.0	1.18	310
4.0	1.58	174
5.0	1.97	111



30°

Fixed UGR<16



 2118.564-LEA-09B-HE
 2118.659F-LEA-09B-HE


H(m)	D(m)	E(lx)
30°		
1.0	0.51	2466
2.0	1.02	616
3.0	1.54	274
4.0	2.05	154
5.0	2.56	98



40°

Fixed UGR<19



 2118.564-LEA-09B-HE
 2118.659F-LEA-09B-HE


H(m)	D(m)	E(lx)
40°		
1.0	0.75	1275
2.0	1.49	318
3.0	2.24	141
4.0	2.99	79
5.0	3.74	50



50°

Fixed UGR<25

 2118.564-LEA-09B-HE
 2118.659F-LEA-09B-HE




H(m)	D(m)	E(lx)
50°		
1.0	1.00	745
2.0	2.00	186
3.0	2.99	82
4.0	3.99	46
5.0	4.99	29



50°

Adjustable

2118.565-LEA-09B
2118.660F-LEA-09B





H(m)	D(m)	E(lx)
50°		
1.0	0.95	637
2.0	1.89	159
3.0	2.84	70
4.0	3.78	39
5.0	4.73	25



20°

Adjustable

2118.565-LEA-09B-HE
2118.660F-LEA-09B-HE





H(m)	D(m)	E(lx)
20°		
1.0	0.36	3011
2.0	0.72	752
3.0	1.08	334
4.0	1.43	188
5.0	1.79	120



30°

Adjustable

2118.565-LEA-09B-HE
2118.660F-LEA-09B-HE





H(m)	D(m)	E(lx)
30°		
1.0	0.49	2518
2.0	0.98	629
3.0	1.48	279
4.0	1.97	157
5.0	2.46	100



40°

Adjustable

2118.565-LEA-09B-HE
2118.660F-LEA-09B-HE





H(m)	D(m)	E(lx)
40°		
1.0	0.72	1299
2.0	1.44	324
3.0	2.16	144
4.0	2.88	81
5.0	3.60	51



50°

Adjustable

2118.565-LEA-09B-HE
2118.660F-LEA-09B-HE





H(m)	D(m)	E(lx)
50°		
1.0	0.92	784
2.0	1.83	196
3.0	2.75	87
4.0	3.66	49
5.0	4.58	31



Wallwash

2318.100-LEA-09B
2318.200F-LEA-09B





H(m)	D(m)	E(lx)
Wallwash		
1.0	0.48	543
2.0	0.96	135
3.0	1.45	60
4.0	1.93	33
5.0	2.41	21



Wallwash



2318.100-LEA-09B-HE
2318.200F-LEA-09B-HE



H(m)	D(m)	E(lx)
Wallwash		
1.0	0.50	630
2.0	1.01	157
3.0	1.51	70
4.0	2.02	39
5.0	2.52	25

**20°**



Fixed UGR<19

2218.117-LEA-09B
2218.208A-LEA-09B

H(m)	D(m)	E(lx)
20°		
1.0	0.36	2273
2.0	0.72	568
3.0	1.08	252
4.0	1.44	142
5.0	1.80	90

**25°**



Fixed UGR<16

2218.117-LEA-09B
2218.208A-LEA-09B

H(m)	D(m)	E(lx)
25°		
1.0	0.47	1979
2.0	0.95	494
3.0	1.42	219
4.0	1.89	123
5.0	2.36	79

**35°**



Fixed UGR<16

2218.117-LEA-09B
2218.208A-LEA-09B

H(m)	D(m)	E(lx)
35°		
1.0	0.67	1025
2.0	1.35	256
3.0	2.02	113
4.0	2.70	64
5.0	3.37	41

**50°**



Fixed UGR<19

2218.117-LEA-09B
2218.208A-LEA-09B

H(m)	D(m)	E(lx)
50°		
1.0	0.93	648
2.0	1.87	162
3.0	2.80	72
4.0	3.73	40
5.0	4.67	25

**20°**



Fixed UGR<22

2218.117-LEA-09B-HE
2218.208A-LEA-09B-HE

H(m)	D(m)	E(lx)
20°		
1.0	0.37	2861
2.0	0.73	715
3.0	1.10	317
4.0	1.47	178
5.0	1.83	114

**30°**



Fixed UGR<19

2218.117-LEA-09B-HE
2218.208A-LEA-09B-HE

H(m)	D(m)	E(lx)
30°		
1.0	0.50	2289
2.0	1.01	572
3.0	1.51	254
4.0	2.01	143
5.0	2.51	91

**40°**



Fixed UGR<19

2218.117-LEA-09B-HE
2218.208A-LEA-09B-HE

H(m)	D(m)	E(lx)
40°		
1.0	0.73	1226
2.0	1.46	306
3.0	2.18	136
4.0	2.91	76
5.0	3.64	49

**50°**



Fixed UGR<22

2218.117-LEA-09B-HE
2218.208A-LEA-09B-HE

H(m)	D(m)	E(lx)
50°		
1.0	0.97	764
2.0	1.94	191
3.0	2.91	84
4.0	3.88	47
5.0	4.85	30

 20°



Adjustable

 2218.118-LEA-09B
 2218.209A-LEA-09B


H(m)	D(m)	E(lx)
20°		
1.0	0.35	2414
2.0	0.69	603
3.0	1.04	268
4.0	1.38	150
5.0	1.73	96

 25°



Adjustable

 2218.118-LEA-09B
 2218.209A-LEA-09B


H(m)	D(m)	E(lx)
25°		
1.0	0.47	1894
2.0	0.94	473
3.0	1.41	210
4.0	1.88	118
5.0	2.35	75

 35°



Adjustable

 2218.118-LEA-09B
 2218.209A-LEA-09B


H(m)	D(m)	E(lx)
35°		
1.0	0.66	1005
2.0	1.31	251
3.0	1.97	111
4.0	2.62	62
5.0	3.28	40

 50°



Adjustable

 2218.118-LEA-09B
 2218.209A-LEA-09B


H(m)	D(m)	E(lx)
50°		
1.0	0.94	628
2.0	1.87	157
3.0	2.81	69
4.0	3.75	39
5.0	4.68	25

 20°



Adjustable

 2218.118-LEA-09B-HE
 2218.209A-LEA-09B-HE


H(m)	D(m)	E(lx)
20°		
1.0	0.35	2993
2.0	0.70	748
3.0	1.05	332
4.0	1.41	187
5.0	1.75	119

 30°



Adjustable

 2218.118-LEA-09B-HE
 2218.209A-LEA-09B-HE


H(m)	D(m)	E(lx)
30°		
1.0	0.49	2454
2.0	0.98	613
3.0	1.47	272
4.0	1.96	153
5.0	2.45	98

 40°



Adjustable

 2218.118-LEA-09B-HE
 2218.209A-LEA-09B-HE


H(m)	D(m)	E(lx)
40°		
1.0	0.71	1217
2.0	1.42	304
3.0	2.13	135
4.0	2.85	76
5.0	3.56	48

 50°

Adjustable

 2218.118-LEA-09B-HE
 2218.209A-LEA-09B-HE


H(m)	D(m)	E(lx)
50°		
1.0	0.95	729
2.0	1.89	182
3.0	2.84	81
4.0	3.78	45
5.0	4.73	29