

# AQUA SERIES (EU)

AQUA series is designed with powerful IP65 function, along with soft and bright visual effects, creating the interaction of light and shadow, fully presenting the charm of the space. Aqua series is ideal for entrance, stairway, bathrooms and outdoor corridor.

Material: Aluminum die cast heatsink, aluminum die cast trim, trim can be made into black & white.





This waterproof recessed light is designed for humid environments, making it perfect for bathrooms, kitchens, balconies, and corridors. It offers reliable, efficient lighting and comes in three sizes: large, medium, and small, to fit various spaces. Whether for a cozy ambiance or functional lighting, this light is an excellent choice to brighten any area.








Colours


Bezel : Black  White

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
 2118.147	13W	350 mA	1332 lm	858 lm	24°/45° (Reflector)	3000K	90+

Dimmable



Optional Accessory





--- honeycomb louver --- Waterproof junction box


IES




Fixed UGR<13  
2118.147





H(m)	D(m)	E(lx)
24°		
1.0	0.42	3387
2.0	0.84	846
3.0	1.26	376
4.0	1.68	211
5.0	2.09	135



 Cut out : 80mm



Fixed UGR<19  
2118.147



H(m)	D(m)	E(lx)
45°		
1.0	0.82	1526
2.0	1.64	381
3.0	2.46	169
4.0	3.28	95
5.0	4.10	61



Colours

Bezel : Black  White

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
 2118.148-HE	15W	450 mA	2445 lm	1845 lm	45°/60° (Reflector)	3000K	90+

Dimmable



Optional Accessory





--- Waterproof junction box

IES





Fixed UGR<19

2118.148-HE



H(m)	D(m)	E(lx)
45°		
1.0	0.85	3084
2.0	1.71	771
3.0	2.56	342
4.0	3.42	192
5.0	4.27	123





 Cut out : 110mm



Fixed UGR<19

2118.148-HE



H(m)	D(m)	E(lx)
60°		
1.0	1.12	2241
2.0	2.23	560
3.0	3.35	249
4.0	4.47	140
5.0	5.58	89



### Colours

Bezel : Black  White

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
 2318.185-HE	25W	750 mA	4076 lm	2979 lm	48°/66° (Reflector)	3000K	90+

### Dimmable



### Optional Accessory





--- Waterproof junction box

### IES





Fixed UGR<16

2318.185-HE



H(m)	D(m)	E(lx)
48°		
1.0	0.90	4734
2.0	1.80	1183
3.0	2.70	526
4.0	3.61	295
5.0	4.51	189





 Cut out : 130mm



Fixed UGR<19

2318.185-HE



H(m)	D(m)	E(lx)
66°		
1.0	1.29	2722
2.0	2.58	680
3.0	3.87	302
4.0	5.17	170
5.0	6.46	108

