

EPIC SERIES (EU)



EPIC (EU)

Designed base on the concept of “light engine modularization”, making EPIC series possible to be more flexible, more practical and expandable.

The features are as follows:

- * Modularized design—easy maintenance & replacement
- * Maximize common components to reduce stock cost
- * Speed up the progress of new series development in the future
- * Interchangeable design to increase product flexibility
- * Set up design norms by modularization, minimize possible faults



EPIC 65/85/110/135
Recessed downlights



ACOT-68



ACOT-69-WCW
Tunable white



ACOT-70
ACOT-70A Narrow beam
ACOT-70-WCW Tunable white

	65 Fixed	65 Adjustable	85 Fixed	85 Adjustable	85 Wallwash
Round					
Trim					
Trimless					
Square					
Trim					
Trimless					



LEE-15
LEE-15A Narrow beam
LEE-15-DW Dim to warm



ACOT-72
ACOT-72-WCW Tunable white



ACOT-73
ACOT-73-WCW Tunable white

	110 Fixed	110 Adjustable	110 Wallwash	135 Fixed	135 Adjustable	135 Wallwash
Round						
Trim						
Trimless						
Square						
Trim						
Trimless						



EPIC (EU)





Prevent light leak

Adding an extra component to the fixture prevent people seeing through the fixture a very tender thought from our designer



Material and color

Trim: Aluminium die cast, White/ Black




Baffle finish :

1. Aluminium die cast : White/ Black/ Haze/ Gold
2. Plastic : Chrome




Optics

Deep baffle design helps reduce glare, equipped with special selected lens, the light is evenly spread to achieve the beam angle needed, making EPIC a unique series.



Wallwash

EPIC a wallwash enables even illumination on the target wall without shadows. It supplies an overall effect that is clean and elegant. Generally speaking, the distance between the lighting fixture and the height of the illuminated wall ranges from 1/3 to 1/5. This wallwash function; not only broadens the illumination effect with smooth lights performance but also makes the entire area feels brighter. When combining with other function fixtures together, it can form a fusion of beauty.



RECOMMENDED
DISTANCES (Meter)

A : H : B 0.75 : <3.5 : 0.75 (m)



Advantage of light With narrow beam

The narrower the angle, the better the condensing effect. As the beam is more focused, it maintains its intensity over greater distances, allowing the light to travel further. It helps to effectively reduce the overflow of light, make the light spot slender and clean, and achieve an excellent focused lighting effect. It is suitable for where the application needs narrow beam lights, such as artworks, indoor landscapes, museums, galleries, and showcases.



Ultra narrow beam




Standard beam



Striped glass Woven glass Diffusion sheet Honeycomb louver

With more options to the accessories, epic adds more
Flexibility and freedom for the lighting designer.
Honeycomb reduces glare; strip glass creates oval distribution;
Diffusion sheet & woven glass soften and even spread the light.



Lens (no accessory) Striped glass Woven glass Diffusion sheet Honeycomb louver



Dim to warm

This light engine features Dim to Warm, the ultimate in dimming comfort, where the light changes its colour temperature according to the dimming curve; the darker the light, the warmer the light. Like a sunset effect, the gradual change replicates the transition from a comfortable ambience to a relaxing and soothing environment.

Dim to Warm is the term used to describe the function of LEDs to reduce the colour temperature (CCT) of the light as it dims, from 3000K at 100% to 1800K at nearly 0%.

The light provides a relaxing ambience for a typical evening dining experience, reading in bed, a moody hotel lobby or bar environment. By moving from dim to warm, we provide a light source that is alert and bright when cooking or working, then dimmed to provide a warm ambience for hosting and relaxing in the evening.

Tunable white

Changes in light colour can have a significant impact on our mood. This light engine with Tunable White drivers allows the colour temperature to be continuously adjusted from 2700 K (warm light) to 6500 K (cool light) to provide uniform, high quality lighting that dynamically adjusts to the time of day or ambient brightness. It allows designers to simulate daylight for productivity and well-being, retailers to influence shoppers' behaviour, and luminaire manufacturers to simulate the familiar glow and dimming of incandescent lamps.



Easy installation

Easy to replace, quick to assemble and completely tool-free.



Hole size doesn't match? No worries!

Your installation “Rescue Ring” is here!

During lighting installation, one of the most frustrating issues is dealing with old ceiling cutouts that don't match the new fixture size—or when the hole was accidentally cut too large.

Now you don't need to redo the ceiling or settle for uneven gaps.

Our Goof ring is designed exactly for this situation!


One Goof ring is all you need for a perfect fit!

Whether you're reusing an existing opening or correcting a cutting mistake, this "Goof ring" ensures your lighting still looks flawless, consistent, and beautifully integrated.

Simply install the trim ring before mounting the light.

It helps you:

- Perfectly cover oversized cutouts
- Hide installation errors for a clean finish
- Blend seamlessly with your light fixture
- Install quickly—saving time and effort



* This accessory is also compatible with various related sizes of recessed downlights.




EP85-GOOFRING-4

for **85**




EP110-GOOFRING-4

for **110**



EP110-GOOFRING-6

for **110**





EPIC-65 ▶

Round / Square

Fixed

Adjustable

EPIC-65 Round-Fixed





EPIC-65-RTF
EPIC-65-RTL



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.100-ACOT-68	10W	250 mA	913 lm	766 lm	20°/40°/55° (Lens)	3000K	90+
 2118.100-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.200F-ACOT-68	10W	250 mA	913 lm	766 lm	20°/40°/55° (Lens)	3000K	90+
 2118.200F-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+




Dimmable



Optional Accessory



IES



EPIC-65 Round-Adjustable


EPIC-65-RTA
EPIC-65-RTL




Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐


Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.101-ACOT-68	10W	250 mA	913 lm	767 lm	20°/40°/55° (Lens)	3000K	90+
 2118.101-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.201F-ACOT-68	10W	250 mA	913 lm	767 lm	20°/40°/55° (Lens)	3000K	90+
 2118.201F-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+




Cut out : 60mm (Trim)



Cut out : 60mm (Trim)




Cut out : 60mm (Trimless)



Cut out : 60mm (Trimless)

Dimmable



Optional Accessory





IES



Adjustable

2118.101-ACOT-68
2118.201F-ACOT-68





H(m)	D(m)	E(lx)
20°		
1.0	0.35	4878
2.0	0.69	1220
3.0	1.04	542
4.0	1.38	305
5.0	1.73	195



Adjustable

2118.101-ACOT-68
2118.201F-ACOT-68





H(m)	D(m)	E(lx)
40°		
1.0	0.75	1540
2.0	1.50	384
3.0	2.26	171
4.0	3.01	96
5.0	3.76	61



Adjustable

2118.101-ACOT-68
2118.201F-ACOT-68



H(m)	D(m)	E(lx)
55°		
1.0	0.95	1017
2.0	1.89	254
3.0	2.84	113
4.0	3.78	63
5.0	4.73	40

EPIC-65 Square-Fixed





EPIC-65-STF
EPIC-65-STLF



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.103-ACOT-68	10W	250 mA	913 lm	796 lm	20°/40°/55° (Lens)	3000K	90+
 2118.103-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.203A-ACOT-68	10W	250 mA	913 lm	796 lm	20°/40°/55° (Lens)	3000K	90+
 2118.203A-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+





Dimmable





Optional Accessory





IES



H(m)	D(m)	E(lx)
20°		
1.0	0.35	4705
2.0	0.70	1176
3.0	1.05	522
4.0	1.39	294
5.0	1.74	188



H(m)	D(m)	E(lx)
40°		
1.0	0.77	1558
2.0	1.53	389
3.0	2.30	173
4.0	3.07	97
5.0	3.83	62



H(m)	D(m)	E(lx)
55°		
1.0	0.93	1020
2.0	1.87	255
3.0	2.80	113
4.0	3.73	63
5.0	4.67	40

EPIC-65 Square-Adjustable


EPIC-65-STA
EPIC-65-STLA




Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒



Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.104-ACOT-68	10W	250 mA	913 lm	755 lm	20°/40°/55° (Lens)	3000K	90+
 2118.104-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.204A-ACOT-68	10W	250 mA	913 lm	755 lm	20°/40°/55° (Lens)	3000K	90+
 2118.204A-ACOT-69-WCW	10W	250 mA	680-882 lm	-	20°/40°/55° (Lens)	2700-6500K	90+





Cut out : 60x60mm (Trim)



Cut out : 60x60mm (Trimless)



Cut out : 60x60mm (Trimless)



Cut out : 60x60mm (Trimless)


Dimmable



Optional Accessory



ACSG-5
Striped PC sheet



ACHO-6
Honeycomb louver



ACDS-3
Diffusion sheet



ACWG-6
Woven glass





ACOT-107
Suction cup

IES



Adjustable

2118.104-ACOT-68
2118.204A-ACOT-68





H(m)	D(m)	E(lx)
20°		
1.0	0.35	4619
2.0	0.69	1155
3.0	1.04	513
4.0	1.38	288
5.0	1.73	184



Adjustable

2118.104-ACOT-68
2118.204A-ACOT-68





H(m)	D(m)	E(lx)
40°		
1.0	0.76	1521
2.0	1.52	380
3.0	2.27	169
4.0	3.03	95
5.0	3.79	60



Adjustable

2118.104-ACOT-68
2118.204A-ACOT-68



H(m)	D(m)	E(lx)
55°		
1.0	0.95	1021
2.0	1.90	255
3.0	2.85	113
4.0	3.81	63
5.0	4.76	40



EPIC-85 ▶

Round / Square

Fixed
Adjustable
Wallwash

EPIC-85 Round-Fixed


EPIC-85-RTF
EPIC-85-RTL



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐


Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.106-ACOT-70A	10W	800 mA	774 lm	526 lm	13° (Lens)	3000K	90+
2118.106-ACOT-70	12W	350 mA	1446 lm	1265 lm	30°/50°/60° (Lens)	3000K	90+
2118.106-ACOT-70-WCW	13W	350 mA	1143-1356 lm	622-725 lm	30°/40°/50° (Lens)	2700-6500K	90+
Trimless							
 2118.206F-ACOT-70A	10W	800 mA	774 lm	526 lm	13° (Lens)	3000K	90+
2118.206F-ACOT-70	12W	350 mA	1446 lm	1265 lm	30°/50°/60° (Lens)	3000K	90+
2118.206F-ACOT-70-WCW	13W	350 mA	1143-1356 lm	622-725 lm	30°/40°/50° (Lens)	2700-6500K	90+



Dimmable





Optional Accessory





13°

Fixed UGR<10



2118.106-ACOT-70A
2118.206F-ACOT-70A

H(m)	D(m)	E(lx)
13°		
1.0	0.23	5576
2.0	0.46	1394
3.0	0.70	619
4.0	0.93	348
5.0	1.16	223



30°

Fixed UGR<19



2118.106-ACOT-70
2118.206F-ACOT-70

H(m)	D(m)	E(lx)
30°		
1.0	0.50	3470
2.0	1.01	867
3.0	1.51	385
4.0	2.01	216
5.0	2.52	138



50°

Fixed UGR<19



2118.106-ACOT-70
2118.206F-ACOT-70

H(m)	D(m)	E(lx)
50°		
1.0	0.92	1862
2.0	1.84	465
3.0	2.76	206
4.0	3.67	116
5.0	4.59	74



60°

Fixed UGR<22

2118.106-ACOT-70
2118.206F-ACOT-70

H(m)	D(m)	E(lx)
60°		
1.0	1.14	1301
2.0	2.27	325
3.0	3.41	144
4.0	4.54	81
5.0	5.68	52

EPIC-85 Round-Adjustable



EPIC-85-RTA
EPIC-85-RTLA




Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐


Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.107-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.107-ACOT-70	12W	350 mA	1446 lm	1124 lm	30°/50°/60° (Lens)	3000K	90+
2118.107-ACOT-70-WCW	13W	350 mA	1143-1356 lm	607-707 lm	30°/40°/50° (Lens)	2700-6500K	90+
Trimless							
 2118.207F-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.207F-ACOT-70	12W	350 mA	1446 lm	1124 lm	30°/50°/60° (Lens)	3000K	90+
2118.207F-ACOT-70-WCW	13W	350 mA	1143-1356 lm	607-707 lm	30°/40°/50° (Lens)	2700-6500K	90+



Dimmable





Optional Accessory





Adjustable

2118.107-ACOT-70
2118.207F-ACOT-70





H(m)	D(m)	E(lx)
30°		
1.0	0.49	3409
2.0	0.98	852
3.0	1.46	378
4.0	1.95	213
5.0	2.44	136



Adjustable

2118.107-ACOT-70
2118.207F-ACOT-70





H(m)	D(m)	E(lx)
50°		
1.0	0.87	1876
2.0	1.73	469
3.0	2.60	208
4.0	3.46	117
5.0	4.33	75



Adjustable

2118.107-ACOT-70
2118.207F-ACOT-70



H(m)	D(m)	E(lx)
60°		
1.0	1.06	1279
2.0	2.12	319
3.0	3.18	142
4.0	4.24	79
5.0	5.30	51

EPIC-85 Round-Wallwash

EPIC-85-RTW
EPIC-85-RTLW




Colours

Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.108-ACOT-70	12W	350 mA	1446 lm	654 lm	Wallwash (Lens)	3000K	90+
2118.108-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	Wallwash (Lens)	2700-6500K	90+
Trimless							
 2118.208F-ACOT-70	12W	350 mA	1446 lm	654 lm	Wallwash (Lens)	3000K	90+
2118.208F-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	Wallwash (Lens)	2700-6500K	90+

* Wallwash lens — best optical matching angle: 15°



Dimmable




IES



Wallwash

2118.108-ACOT-70
2118.208F-ACOT-70



H(m)	D(m)	E(lx)
Wallwash		
1.0	0.63	1012
2.0	1.27	253
3.0	1.90	112
4.0	2.54	63
5.0	3.17	40



EPIC-85 Square-Fixed



EPIC-85-STF
EPIC-85-STLF



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒


Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.109-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.109-ACOT-70	12W	350 mA	1446 lm	1172 lm	30°/50°/60° (Lens)	3000K	90+
2118.109-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	30°/50°/60° (Lens)	2700-6500K	90+
Trimless							
 2118.209A-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.209A-ACOT-70	12W	350 mA	1446 lm	1172 lm	30°/50°/60° (Lens)	3000K	90+
2118.209A-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	30°/50°/60° (Lens)	2700-6500K	90+



Dimmable





Optional Accessory



 30°

Fixed UGR<13

2118.109-ACOT-70
2118.209A-ACOT-70





H(m)	D(m)	E(lx)
30°		
1.0	0.51	3246
2.0	1.02	811
3.0	1.53	360
4.0	2.04	202
5.0	2.55	129

 50°

Fixed UGR<16

2118.109-ACOT-70
2118.209A-ACOT-70





H(m)	D(m)	E(lx)
50°		
1.0	0.88	1889
2.0	1.76	472
3.0	2.64	209
4.0	3.52	118
5.0	4.40	75

 60°

Fixed UGR<19

2118.109-ACOT-70
2118.209A-ACOT-70



H(m)	D(m)	E(lx)
60°		
1.0	1.09	1289
2.0	2.18	322
3.0	3.26	143
4.0	4.35	80
5.0	5.44	51

EPIC-85 Square-Adjustable


EPIC-85-STA
EPIC-85-STLA




Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.110-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.110-ACOT-70	12W	350 mA	1446 lm	1135 lm	30°/50°/60° (Lens)	3000K	90+
2118.110-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	30°/50°/60° (Lens)	2700-6500K	90+
Trimless							
 2118.210A-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2118.210A-ACOT-70	12W	350 mA	1446 lm	1135 lm	30°/50°/60° (Lens)	3000K	90+
2118.210A-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	30°/50°/60° (Lens)	2700-6500K	90+




 Cut out : 80x80mm (Trim)




 Cut out : 80x80mm (Trimless)

Dimmable





Optional Accessory



 30°

Adjustable

2118.110-ACOT-70
2118.210A-ACOT-70





H(m)	D(m)	E(lx)
30°		
1.0	0.49	3438
2.0	0.98	859
3.0	1.48	382
4.0	1.97	214
5.0	2.46	137

 50°

Adjustable

2118.110-ACOT-70
2118.210A-ACOT-70





H(m)	D(m)	E(lx)
50°		
1.0	0.89	1812
2.0	1.79	453
3.0	2.68	201
4.0	3.57	113
5.0	4.46	72

 60°

Adjustable

2118.110-ACOT-70
2118.210A-ACOT-70



H(m)	D(m)	E(lx)
60°		
1.0	1.08	1263
2.0	2.16	315
3.0	3.24	140
4.0	4.32	78
5.0	5.40	50

EPIC-85 Square-Wallwash

EPIC-85-STW
EPIC-85-STLW





Colours

Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.111-ACOT-70	12W	350 mA	1446 lm	627 lm	Wallwash (Lens)	3000K	90+
2118.111-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	Wallwash (Lens)	2700-6500K	90+
Trimless							
 2118.211A-ACOT-70	12W	350 mA	1446 lm	627 lm	Wallwash (Lens)	3000K	90+
2118.211A-ACOT-70-WCW	13W	350 mA	11143-1356 lm	-	Wallwash (Lens)	2700-6500K	90+

* Wallwash lens — best optical matching angle: 15°



Dimmable





IES



Wallwash

2118.111-ACOT-70
2118.211A-ACOT-70



H(m)	D(m)	E(lx)
Wallwash		
1.0	0.63	995
2.0	1.26	248
3.0	1.89	110
4.0	2.52	62
5.0	3.15	39





EPIC-110 ▶

Round / Square

Fixed
Adjustable
wallwash

EPIC-110 Round-Fixed

EPIC-110-RTF
EPIC-110-RTL



Colours

Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Haze ☐ Gold ☒ Chrome ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.187-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.187-LEE-15	17W	500 mA	2004 lm	1697 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.187-LEE-15-DW	16W	450 mA	34-1507 lm	1200 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.187-ACOT-72	25W	700 mA	2873 lm	2255 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.187-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700-6500K	90+
Trimless							
 2018.259F-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.259F-LEE-15	17W	500 mA	2004lm	1697 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.259F-LEE-15-DW	16W	450 mA	34-1507 lm	1200 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.259F-ACOT-72	25W	700 mA	2873 lm	2255 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.259F-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700-6500K	90+

2018.187-LEE-15
2018.187-LEE-15A
2018.187-LEE-15-DW



 Cut out : 100mm (Trim)

Dimmable



Optional Accessory



SG7-1
Striped glass



H7-1
Honeycomb louver



DS7-1
Diffusion sheet



WG7-1
Woven glass



ACOT-109
Suction cup



ACOT-82
MR16 Accessory kits




ACOT-83
GU10 Accessory kits




PJ-0079
MR16&GU10 Accessory

2018.187-ACOT-72
2018.187-ACOT-72-WCW




☞ Cut out : 100mm (Trim)

2018.259F-LEE-15
2018.259F-LEE-15A
2018.259F-LEE-15-DW



☞ Cut out : 100mm (Trimless)

2018.259F-ACOT-72
2018.259F-ACOT-72-WCW





☞ Cut out : 100mm (Trimless)

IES



Fixed UGR<10

2018.187-LEE-15
2018.259F-LEE-15





H(m)	D(m)	E(lx)
20°		
1.0	0.38	8808
2.0	0.77	2202
3.0	1.15	978
4.0	1.53	550
5.0	1.91	352



Fixed UGR<10

2018.187-LEE-15
2018.259F-LEE-15





H(m)	D(m)	E(lx)
30°		
1.0	0.59	5545
2.0	1.18	1386
3.0	1.77	616
4.0	2.35	346
5.0	2.94	221



Fixed UGR<13

2018.187-LEE-15
2018.259F-LEE-15





H(m)	D(m)	E(lx)
45°		
1.0	0.79	3325
2.0	1.58	831
3.0	2.37	369
4.0	3.16	207
5.0	3.94	133



Fixed UGR<19

2018.187-LEE-15
2018.259F-LEE-15





H(m)	D(m)	E(lx)
55°		
1.0	1.05	2051
2.0	2.11	512
3.0	3.16	227
4.0	4.22	128
5.0	5.27	82



Fixed UGR<16

2018.187-ACOT-72
2018.259F-ACOT-72





H(m)	D(m)	E(lx)
30°		
1.0	0.58	5365
2.0	1.15	1341
3.0	1.73	596
4.0	2.31	335
5.0	2.88	214



Fixed UGR<16

2018.187-ACOT-72
2018.259F-ACOT-72





H(m)	D(m)	E(lx)
40°		
1.0	0.74	4751
2.0	1.49	1188
3.0	2.23	527
4.0	2.98	296
5.0	3.72	190



Fixed UGR<19

2018.187-ACOT-72
2018.259F-ACOT-72





H(m)	D(m)	E(lx)
50°		
1.0	0.94	3396
2.0	1.87	848
3.0	2.81	377
4.0	3.75	212
5.0	4.68	135



Fixed UGR<22

2018.187-ACOT-72
2018.259F-ACOT-72



H(m)	D(m)	E(lx)
60°		
1.0	1.15	2381
2.0	2.31	595
3.0	3.46	264
4.0	4.62	148
5.0	5.77	95

EPIC-110 Round-Adjustable


EPIC-110-RTA
EPIC-110-RTLA



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.191-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.191-LEE-15	17W	500 mA	2004 lm	1702 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.191-LEE-15-DW	16W	450 mA	34-1507 lm	1200 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.191-ACOT-72	25W	700 mA	2873 lm	2207 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.191-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700-6500K	90+
Trimless							
 2018.260F-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.260F-LEE-15	17W	500 mA	2004 lm	1702 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.260F-LEE-15-DW	16W	450 mA	34-1507 lm	1200 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.260F-ACOT-72	25W	700 mA	2873 lm	2207 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.260F-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700-6500K	90+




Dimmable



Optional Accessory




2018.191-ACOT-72
2018.191-ACOT-72-WCW




 Cut out : 100mm (Trim)

2018.260F-LEE-15
2018.260F-LEE-15A
2018.260F-LEE-15-DW



 Cut out : 100mm (Trimless)

2018.260F-ACOT-72
2018.260F-ACOT-72-WCW





 Cut out : 100mm (Trimless)

IES



Adjustable

2018.191-LEE-15
2018.260F-LEE-15





H(m)	D(m)	E(lx)
20°		
1.0	0.38	8971
2.0	0.77	2243
3.0	1.15	996
4.0	1.53	560
5.0	1.92	358



Adjustable

2018.191-LEE-15
2018.260F-LEE-15





H(m)	D(m)	E(lx)
30°		
1.0	0.58	5663
2.0	1.17	1416
3.0	1.75	629
4.0	2.34	353
5.0	2.92	226



Adjustable

2018.191-LEE-15
2018.260F-LEE-15





H(m)	D(m)	E(lx)
45°		
1.0	0.80	3234
2.0	1.60	808
3.0	2.40	359
4.0	3.20	202
5.0	4.00	129



Adjustable

2018.191-LEE-15
2018.260F-LEE-15





H(m)	D(m)	E(lx)
55°		
1.0	1.07	1995
2.0	2.14	498
3.0	3.21	221
4.0	4.28	124
5.0	5.35	79



Adjustable

2018.191-ACOT-72
2018.260F-ACOT-72





H(m)	D(m)	E(lx)
30°		
1.0	0.55	5265
2.0	1.10	1316
3.0	1.65	585
4.0	2.20	329
5.0	2.75	210



Adjustable

2018.191-ACOT-72
2018.260F-ACOT-72





H(m)	D(m)	E(lx)
40°		
1.0	0.74	4677
2.0	1.47	1169
3.0	2.21	519
4.0	2.95	292
5.0	3.68	187



Adjustable

2018.191-ACOT-72
2018.260F-ACOT-72





H(m)	D(m)	E(lx)
50°		
1.0	0.92	3378
2.0	1.84	844
3.0	2.76	375
4.0	3.68	211
5.0	4.61	135



Adjustable

2018.191-ACOT-72
2018.260F-ACOT-72



H(m)	D(m)	E(lx)
60°		
1.0	1.13	2374
2.0	2.26	593
3.0	3.39	263
4.0	4.52	148
5.0	5.65	94

EPIC-110 Round-Wallwash

EPIC-110-RTW
EPIC-110-RTLW




Colours


Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.192-LEE-15	17W	500 mA	2004 lm	1100 lm	Wallwash (Lens)	3000K	90+
2018.192-LEE-15-DW	16W	450 mA	34-1507 lm	713 lm	Wallwash (Lens)	1800-3000K	90+
 2018.192-ACOT-72	25W	700 mA	2873 lm	1385 lm	Wallwash (Lens)	3000K	90+
2018.192-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	Wallwash (Lens)	2700-6500K	90+
Trimless							
 2018.261F-LEE-15	17W	500 mA	2004 lm	1100 lm	Wallwash (Lens)	3000K	90+
2018.261F-LEE-15-DW	16W	450 mA	34-1507 lm	713 lm	Wallwash (Lens)	1800-3000K	90+
 2018.261F-ACOT-72	25W	700 mA	2873 lm	1385 lm	Wallwash (Lens)	3000K	90+
2018.261F-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	Wallwash (Lens)	2700-6500K	90+


* Wallwash lens — best optical matching angle: 36°




Cut out : 100mm (Trim)



Cut out : 100mm (Trim)



Cut out : 100mm (Trimless)



Cut out : 100mm (Trimless)

Dimmable





IES



Wallwash

2018.192-LEE-15
2018.261F-LEE-15





H(m)	D(m)	E(lx)
Wallwash		
1.0	0.77	1360
2.0	1.54	340
3.0	2.32	151
4.0	3.09	85
5.0	3.86	54



Wallwash

2018.192-ACOT-72
2018.261F-ACOT-72



H(m)	D(m)	E(lx)
Wallwash		
1.0	0.85	1455
2.0	1.17	363
3.0	2.56	161
4.0	3.41	90
5.0	4.27	58



EPIC-110 Square-Fixed

EPIC-110-STF
EPIC-110-STLF



Colours


Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Haze ☐ Gold ☒ Chrome ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.188-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.188-LEE-15	17W	500 mA	2004 lm	1639 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.188-LEE-15-DW	16W	450 mA	34-1507 lm	1212 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.188-ACOT-72	25W	700 mA	2873 lm	2239 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.188-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700K-6500K	90+
Trimless							
 2018.264A-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.264A-LEE-15	17W	500 mA	2004lm	1639 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.264A-LEE-15-DW	16W	450 mA	34-1507 lm	1212 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.264A-ACOT-72	25W	700 mA	2873 lm	2239 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.264A-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700K-6500K	90+

2018.188-LEE-15
2018.188-LEE-15A
2018.188-LEE-15-DW



 Cut out : 100x100mm (Trim)

Dimmable



Optional Accessory



SG7-1
Striped glass



H7-1
Honeycomb louver



DS7-1
Diffusion sheet



WG7-1
Woven glass



ACOT-109
Suction cup



ACOT-82
MR16 Accessory kits




ACOT-83
GU10 Accessory kits




PJ-0079
MR16&GU10 Accessory

2018.188-ACOT-72
2018.188-ACOT-72-WCW




 Cut out : 100x100mm (Trim)

2018.264A-LEE-15
2018.264A-LEE-15A
2018.264A-LEE-15-DW



 Cut out : 100x100mm (Trimless)

2018.264A-ACOT-72
2018.264A-ACOT-72-WCW





 Cut out : 100x100mm (Trimless)

IES



Fixed UGR<10

2018.188-LEE-15
2018.264A-LEE-15





H(m)	D(m)	E(lx)
20°		
1.0	0.38	8437
2.0	0.77	2109
3.0	1.15	937
4.0	1.53	527
5.0	1.92	337



Fixed UGR<10

2018.188-LEE-15
2018.264A-LEE-15





H(m)	D(m)	E(lx)
30°		
1.0	0.59	5246
2.0	1.17	1312
3.0	1.76	582
4.0	2.34	327
5.0	2.93	209



Fixed UGR<13

2018.188-LEE-15
2018.264A-LEE-15





H(m)	D(m)	E(lx)
45°		
1.0	0.82	2999
2.0	1.63	749
3.0	2.45	333
4.0	3.26	187
5.0	4.08	120



Fixed UGR<16

2018.188-LEE-15
2018.264A-LEE-15





H(m)	D(m)	E(lx)
55°		
1.0	1.06	2014
2.0	2.12	503
3.0	3.18	223
4.0	4.25	125
5.0	5.31	80



Fixed UGR<10

2018.188-ACOT-72
2018.264A-ACOT-72





H(m)	D(m)	E(lx)
30°		
1.0	0.57	5456
2.0	1.13	1364
3.0	1.70	606
4.0	2.27	341
5.0	2.84	218



Fixed UGR<10

2018.188-ACOT-72
2018.264A-ACOT-72





H(m)	D(m)	E(lx)
40°		
1.0	0.74	4794
2.0	1.49	1199
3.0	2.23	532
4.0	2.98	299
5.0	3.72	191



Fixed UGR<13

2018.188-ACOT-72
2018.264A-ACOT-72





H(m)	D(m)	E(lx)
50°		
1.0	0.93	3425
2.0	1.85	856
3.0	2.78	380
4.0	3.71	214
5.0	4.64	137



Fixed UGR<16

2018.188-ACOT-72
2018.264A-ACOT-72



H(m)	D(m)	E(lx)
60°		
1.0	1.13	2409
2.0	2.25	602
3.0	3.38	267
4.0	4.50	150
5.0	5.63	96

EPIC-110 Square-Adjustable

EPIC-110-STA
EPIC-110-STLA



Colours


Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Haze ☐ Gold ☒ Chrome ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.195-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.195-LEE-15	17W	500 mA	2004 lm	1616 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.195-LEE-15-DW	16W	450 mA	34-1507 lm	1227 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.195-ACOT-72	25W	700 mA	2873 lm	2208 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.195-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700K-6500K	90+
Trimless							
 2018.265A-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2018.265A-LEE-15	17W	500 mA	2004 lm	1616 lm	20°/30°/45°/55°/65° (Lens)	3000K	90+
2018.265A-LEE-15-DW	16W	450 mA	34-1507 lm	1227 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2018.265A-ACOT-72	25W	700 mA	2873 lm	2208 lm	30°/40°/50°/60° (Lens)	3000K	90+
2018.265A-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/60° (Lens)	2700K-6500K	90+

2018.195-LEE-15
2018.195-LEE-15A
2018.195-LEE-15-DW



 Cut out : 100x100mm (Trim)

Dimmable



Optional Accessory



SG7-1
Striped glass



H7-1
Honeycomb louver



DS7-1
Diffusion sheet



WG7-1
Woven glass



ACOT-109
Suction cup



ACOT-82
MR16 Accessory kits




ACOT-83
GU10 Accessory kits




PJ-0079
MR16&GU10 Accessory

2018.195-ACOT-72
2018.195-ACOT-72-WCW




Cut out : 100x100mm (Trim)

2018.265A-LEE-15
2018.265A-LEE-15A
2018.265A-LEE-15-DW



Cut out : 100x100mm (Trimless)

2018.265A-ACOT-72
2018.265A-ACOT-72-WCW





Cut out : 100x100mm (Trimless)

IES



Adjustable

2018.195-LEE-15
2018.265A-LEE-15





H(m)	D(m)	E(lx)
20°		
1.0	0.38	8345
2.0	0.77	2086
3.0	1.15	927
4.0	1.53	521
5.0	1.91	333



Adjustable

2018.195-LEE-15
2018.265A-LEE-15





H(m)	D(m)	E(lx)
30°		
1.0	0.59	5262
2.0	1.18	1316
3.0	1.77	584
4.0	2.36	328
5.0	2.95	210



Adjustable

2018.195-LEE-15
2018.265A-LEE-15




H(m)	D(m)	E(lx)
45°		
1.0	0.80	3044
2.0	1.60	761
3.0	2.40	338
4.0	3.20	190
5.0	4.01	121



Adjustable

2018.195-LEE-15
2018.265A-LEE-15





H(m)	D(m)	E(lx)
55°		
1.0	1.05	2042
2.0	2.10	510
3.0	3.15	226
4.0	4.20	127
5.0	5.25	81



Adjustable

2018.195-ACOT-72
2018.265A-ACOT-72





H(m)	D(m)	E(lx)
30°		
1.0	0.56	5402
2.0	1.12	1351
3.0	1.68	600
4.0	2.24	337
5.0	2.80	216



Adjustable

2018.195-ACOT-72
2018.265A-ACOT-72





H(m)	D(m)	E(lx)
40°		
1.0	0.74	4744
2.0	1.48	1186
3.0	2.22	527
4.0	2.96	296
5.0	3.71	189



Adjustable

2018.195-ACOT-72
2018.265A-ACOT-72





H(m)	D(m)	E(lx)
50°		
1.0	0.93	3398
2.0	1.86	849
3.0	2.78	377
4.0	3.71	212
5.0	4.64	135



Adjustable

2018.195-ACOT-72
2018.265A-ACOT-72



H(m)	D(m)	E(lx)
60°		
1.0	1.13	2373
2.0	2.27	593
3.0	3.40	263
4.0	4.54	148
5.0	5.67	94

EPIC-110 Square-Wallwash

EPIC-110-STW
EPIC-110-STLW







Colours

Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.196-LEE-15	17W	500 mA	2004 lm	1062 lm	Wallwash (Lens)	3000K	90+
2018.196-LEE-15-DW	16W	450 mA	34-1507 lm	739 lm	Wallwash (Lens)	1800-3000K	90+
 2018.196-ACOT-72	25W	700 mA	2873 lm	1396 lm	Wallwash (Lens)	3000K	90+
2018.196-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	Wallwash (Lens)	2700K-6500K	90+
Trimless							
 2018.266A-LEE-15	17W	500 mA	2004 lm	1062 lm	Wallwash (Lens)	3000K	90+
2018.266A-LEE-15-DW	16W	450 mA	34-1507 lm	739 lm	Wallwash (Lens)	1800-3000K	90+
 2018.266A-ACOT-72	25W	700 mA	2873 lm	1396 lm	Wallwash (Lens)	3000K	90+
2018.266A-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	Wallwash (Lens)	2700K-6500K	90+

* Wallwash lens — best optical matching angle: 36°



Dimmable





IES



Wallwash

2018.196-LEE-15
2018.266A-LEE-15





H(m)	D(m)	E(lx)
Wallwash		
1.0	0.78	1264
2.0	1.56	316
3.0	2.34	140
4.0	3.12	79
5.0	3.90	50



Wallwash

2018.196-ACOT-72
2018.266A-ACOT-72



H(m)	D(m)	E(lx)
Wallwash		
1.0	0.86	1399
2.0	1.72	349
3.0	2.59	155
4.0	3.45	87
5.0	4.31	55





EPIC-135 ▶

Round / Square

Fixed
Adjustable
wallwash

EPIC-135 Round-Fixed

EPIC-135-RTF
EPIC-135-RTL



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.464-ACOT-73	32W	900 mA	3667 lm	3187 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.464-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+
Trimless							
 2018.256F-ACOT-73	32W	900 mA	3667 lm	3187 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.256F-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+

Dimmable





Optional Accessory



IES





Fixed UGR<10
2018.464-ACOT-73
2018.256F-ACOT-73



H(m)	D(m)	E(lx)
20°		
1.0	0.38	16360
2.0	0.75	4090
3.0	1.13	1818
4.0	1.51	1022
5.0	1.88	654





Fixed UGR<10
2018.464-ACOT-73
2018.256F-ACOT-73



H(m)	D(m)	E(lx)
30°		
1.0	0.57	10799
2.0	1.14	2700
3.0	1.70	1200
4.0	2.27	674
5.0	2.84	432





Fixed UGR<13
2018.464-ACOT-73
2018.256F-ACOT-73




H(m)	D(m)	E(lx)
45°		
1.0	0.80	6115
2.0	1.60	1529
3.0	2.40	679
4.0	3.20	382
5.0	4.00	244



Fixed UGR<16
2018.464-ACOT-73
2018.256F-ACOT-73



H(m)	D(m)	E(lx)
55°		
1.0	1.03	3635
2.0	2.06	908
3.0	3.10	403
4.0	4.13	227
5.0	5.16	145



EPIC-135 Round-Adjustable

EPIC-135-RTA
EPIC-135-RTLA



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.463-ACOT-73	32W	900 mA	3667 lm	3139 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.463-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+
Trimless							
 2018.255F-ACOT-73	32W	900 mA	3667 lm	3139 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.255F-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+

Dimmable



Optional Accessory



ACSG-1
Striped glass



ACHO-2
Honeycomb louver



ACDS-6
Diffusion sheet



ACWG-1
Woven glass





ACOT-109
Suction cup

IES



Adjustable

2018.463-ACOT-73
2018.255F-ACOT-73





H(m)	D(m)	E(lx)
20°		
1.0	0.37	16240
2.0	0.75	4060
3.0	1.12	1804
4.0	1.49	1015
5.0	1.86	649



Adjustable

2018.463-ACOT-73
2018.255F-ACOT-73





H(m)	D(m)	E(lx)
30°		
1.0	0.57	10699
2.0	1.14	2675
3.0	1.71	1189
4.0	2.28	668
5.0	2.85	428



Adjustable

2018.463-ACOT-73
2018.255F-ACOT-73





H(m)	D(m)	E(lx)
45°		
1.0	0.80	6115
2.0	1.60	1529
3.0	2.40	679
4.0	3.20	382
5.0	4.00	244




Adjustable


2018.463-ACOT-73
2018.255F-ACOT-73



H(m)	D(m)	E(lx)
55°		
1.0	1.03	3658
2.0	2.07	914
3.0	3.10	406
4.0	4.13	228
5.0	5.16	146



Cut out : 128mm (Trim)



Ø121mm



Cut out : 128mm (Trimless)

EPIC-135 Round-Wallwash

EPIC-135-RTW
EPIC-135-RTLW




Colours


Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2218.146-ACOT-73	32W	900 mA	3667 lm	-	Wallwash (Lens)	3000K	90+
2218.146-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	Wallwash (Lens)	2700K-6500K	90+
Trimless							
 2218.218F-ACOT-73	32W	900 mA	3667 lm	-	Wallwash (Lens)	3000K	90+
2218.218F-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	Wallwash (Lens)	2700K-6500K	90+

* Wallwash lens — best optical matching angle: 36°



 Cut out : 128mm (Trim)



 Cut out : 128mm (Trimless)

Dimmable



B GALLERY

B GALLERY



EPIC-135 Square-Fixed

EPIC-135-STF
EPIC-135-STLF



Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.466-ACOT-73	32W	900 mA	3667 lm	3170 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.466-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+
Trimless							
 2018.258A-ACOT-73	32W	900 mA	3667 lm	3170 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.258A-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+

Dimmable



Optional Accessory



ACSG-1
Striped glass



ACHO-2
Honeycomb louver



ACDS-6
Diffusion sheet



ACWG-1
Woven glass





ACOT-109
Suction cup

IES



Fixed UGR<10

2018.466-ACOT-73
2018.258A-ACOT-73





H(m)	D(m)	E(lx)
20°		
1.0	0.38	15921
2.0	0.75	3980
3.0	1.13	1769
4.0	1.51	995
5.0	1.89	636



Fixed UGR<10

2018.466-ACOT-73
2018.258A-ACOT-73





H(m)	D(m)	E(lx)
30°		
1.0	0.57	10648
2.0	1.13	2662
3.0	1.70	1183
4.0	2.26	665
5.0	2.83	425



Fixed UGR<13

2018.466-ACOT-73
2018.258A-ACOT-73





H(m)	D(m)	E(lx)
45°		
1.0	0.78	6283
2.0	1.56	1571
3.0	2.34	698
4.0	3.11	392
5.0	3.89	251




Fixed UGR<16


2018.466-ACOT-73
2018.258A-ACOT-73



H(m)	D(m)	E(lx)
55°		
1.0	1.02	3744
2.0	2.05	935
3.0	3.07	415
4.0	4.09	234
5.0	5.12	149



Cut out : 128x128mm (Trim)



Cut out : 128x128mm (Trimless)

EPIC-135 Square-Adjustable

EPIC-135-STA
EPIC-135-STLA




Colours

- Bezel : Black ☒ White ☐
- Baffle : Black ☒ White ☐
- Haze ☐ Gold ☒ Chrome ☐

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2018.465-ACOT-73	32W	900 mA	3667 lm	3121 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.465-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+
Trimless							
 2018.257A-ACOT-73	32W	900 mA	3667 lm	3121 lm	20°/30°/45°/55° (Lens)	3000K	90+
2018.257A-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	20°/30°/45°/55° (Lens)	2700K-6500K	90+

Dimmable



Optional Accessory



ACSG-1
Striped glass



ACHO-2
Honeycomb louver



ACDS-6
Diffusion sheet



ACWG-1
Woven glass





ACOT-109
Suction cup

IES



Adjustable

2018.465-ACOT-73
2018.257A-ACOT-73





H(m)	D(m)	E(lx)
20°		
1.0	0.37	16417
2.0	0.74	4104
3.0	1.12	1824
4.0	1.49	1026
5.0	1.86	656



Adjustable

2018.465-ACOT-73
2018.257A-ACOT-73





H(m)	D(m)	E(lx)
30°		
1.0	0.57	10564
2.0	1.13	2641
3.0	1.70	1174
4.0	2.26	660
5.0	2.83	422



Adjustable

2018.465-ACOT-73
2018.257A-ACOT-73





H(m)	D(m)	E(lx)
45°		
1.0	0.80	6180
2.0	1.59	1545
3.0	2.39	686
4.0	3.18	386
5.0	3.98	247




Adjustable


2018.465-ACOT-73
2018.257A-ACOT-73



H(m)	D(m)	E(lx)
55°		
1.0	1.02	3740
2.0	2.04	935
3.0	3.06	415
4.0	4.09	233
5.0	5.11	149



Cut out : 128x128mm (Trim)



Cut out : 128x128mm (Trimless)

EPIC-135 Square-Wallwash

EPIC-135-STW
EPIC-135-STLW




Colours


Bezel : Black ☒ White ☐
Baffle : Black ☒

Article number	Fixture Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2218.147-ACOT-73	32W	900 mA	3667 lm	-	Wallwash (Lens)	3000K	90+
2218.147-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	Wallwash (Lens)	2700K-6500K	90+
Trimless							
 2218.219A-ACOT-73	32W	900 mA	3667 lm	-	Wallwash (Lens)	3000K	90+
2218.219A-ACOT-73-WCW	29W	800 mA	2816-3190 lm	-	Wallwash (Lens)	2700K-6500K	90+

* Wallwash lens — best optical matching angle: 36°



 Cut out : 128x128mm (Trim)



 Cut out : 128x128mm (Trimless)

Dimmable





EPIC-65

EPIC-85



44mm



64mm

ACOT-68

ACOT-69-WCW
Tunable White



62mm

ACOT-70A
Narrow spot



62mm

ACOT-70




62mm


ACOT-70-WCW
Tunable White




ACOT-74-15R
ACOT-74-36R
ACOT-74-50R




LN-004-15R
LN-004-36R
LN-004-50R



ACOT-75-10R



ACOT-75-15R
ACOT-75-36R
ACOT-75-50R



LN-008-15R
LN-008-36R
LN-008-50R



ACCL-3
Clear glass

ACSG-5
Striped glass

ACWG-6
Woven glass



ACDS-3
Diffusion sheet



ACHO-6
Honeycomb louver



ACCL-4
Clear glass

ACSG-4
Striped glass


ACWG-5
Woven glass



ACDS-4
Diffusion sheet



ACHO-5
Honeycomb louver



ACOT-44D

ACOT-46D



ACOT-45D

ACOT-47D



ACOT-50D

ACOT-52D



ACOT-51D

ACOT-53D




ACOT-71A
engine is not
suitable with
wallwash baffles



ACOT-54



ACOT-55



RT-EP65-1

ST-EP65-1



RTL-EP65-1

STL-EP65-1



RT-EP85-1

ST-EP85-1



RTL-EP85-1

STL-EP85-1


EPIC-110

EPIC-135


Light engine




Lens



Accessories



Baffle



Trim

