

STELLAR SERIES (EU)



STELLAR (EU)

STELLAR has an accent lighting sleeve accessory design . it can focus more on the lighting display items. It is the design based on the concept of “light engine modularization”, making STELLAR series possible to be more flexible, more practical and expandable.



STELLAR

Recessed downlights



ACOT-70
ACOT-70A Narrow beam
ACOT-70-WCW Tunable white



LEE-15
LEE-15A Narrow beam
LEE-15-DW Dim to warm



ACOT-72
ACOT-72-WCW Tunable white

85
Adjustable

85
Adjustable

110
Adjustable

110
Adjustable

Gimbal

Trim



Trimless





STELLAR-85 Round-Adjustable

STELLAR-85-RTA2
STELLAR-85-RTLA2



Colours

Bezel : Black ☒ White ☐
Baffle : Black ☒ White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2218.143-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2218.143-ACOT-70	12W	350 mA	1446 lm	1122 lm	25°/35°/45°/55° (Lens)	3000K	90+
2218.143-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	25°/35°/45°/55° (Lens)	2700-6500K	90+
Trimless							
 2218.216F-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2218.216F-ACOT-70	12W	350 mA	1446 lm	1122 lm	25°/35°/45°/55° (Lens)	3000K	90+
2218.216F-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	25°/35°/45°/55° (Lens)	2700-6500K	90+


Dimmable



Optional Accessory



ACSG-4
Striped glass



ACHO-5
Honeycomb louver



ACDS-4
Diffusion sheet



ACWG-5
Woven glass



ACSN-17
Snoot




ACOT-103
MR16 Accessory kits




ACOT-104
GU10 Accessory kits



PK-0250
MR16&GU10 Accessory



⌀ Cut out : 80mm (Trim)





⌀ Cut out : 80mm (Trimless)

IES



Adjustable

2218.143-ACOT-70
2218.216F-ACOT-70





H(m)	D(m)	E(lx)
25°		
1.0	0.48	3840
2.0	0.96	960
3.0	1.43	426
4.0	1.91	240
5.0	2.39	153



Adjustable

2218.143-ACOT-70
2218.216F-ACOT-70





H(m)	D(m)	E(lx)
35°		
1.0	0.60	3107
2.0	1.19	776
3.0	1.79	345
4.0	2.39	194
5.0	3.98	124



Adjustable

2218.143-ACOT-70
2218.216F-ACOT-70





H(m)	D(m)	E(lx)
45°		
1.0	0.85	1887
2.0	1.70	471
3.0	2.55	209
4.0	3.40	117
5.0	4.25	75



Adjustable

2218.143-ACOT-70
2218.216F-ACOT-70



H(m)	D(m)	E(lx)
55°		
1.0	1.09	1281
2.0	2.18	320
3.0	3.27	142
4.0	4.36	80
5.0	5.45	51

STELLAR-85 Round-Adjustable

STELLAR-85-RTAS2
STELLAR-85-RTLAS2



Colours

Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2218.144-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2218.144-ACOT-70	12W	350 mA	1446 lm	1122 lm	25°/30°/45°/55° (Lens)	3000K	90+
2218.144-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	25°/30°/45°/55° (Lens)	2700-6500K	90+
Trimless							
 2218.217F-ACOT-70A	10W	800 mA	774 lm	-	10° (Lens)	3000K	90+
2218.217F-ACOT-70	12W	350 mA	1446 lm	1122 lm	25°/35°/45°/55° (Lens)	3000K	90+
2218.217F-ACOT-70-WCW	13W	350 mA	1143-1356 lm	-	25°/35°/45°/55° (Lens)	2700-6500K	90+


Dimmable



Optional Accessory



ACSG-4
Striped glass



ACHO-5
Honeycomb louver



ACDS-4
Diffusion sheet



ACWG-5
Woven glass




ACOT-103
MR16 Accessory kits




ACOT-104
GU10 Accessory kits



PK-0250
MR16&GU10 Accessory



Ⓢ Cut out : 80mm (Trim)




Ⓢ Cut out : 80mm (Trimless)

IES




Adjustable

2218.144-ACOT-70
2218.217F-ACOT-70



(350mA)




H(m)	D(m)	E(lx)
25°		
1.0	0.42	3766
2.0	0.85	941
3.0	1.27	418
4.0	1.70	235
5.0	2.12	150




Adjustable

2218.144-ACOT-70
2218.217F-ACOT-70



(350mA)




H(m)	D(m)	E(lx)
30°		
1.0	0.55	3078
2.0	1.11	769
3.0	1.66	342
4.0	2.21	192
5.0	2.77	123




Adjustable

2218.144-ACOT-70
2218.217F-ACOT-70



(350mA)




H(m)	D(m)	E(lx)
45°		
1.0	0.80	1874
2.0	1.61	468
3.0	2.41	208
4.0	3.21	117
5.0	4.02	74




Adjustable

2218.144-ACOT-70
2218.217F-ACOT-70



(350mA)



H(m)	D(m)	E(lx)
55°		
1.0	1.03	1247
2.0	2.07	311
3.0	3.10	138
4.0	4.13	77
5.0	5.16	49

STELLAR-110 Round-Adjustable

STELLAR110-RTA
STELLAR110-RTLA



Colours

Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.192-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2118.192-LEE-15	17W	500 mA	2004 lm	1580 lm	20°/30°/45°/55° (Lens)	3000K	90+
2118.192-LEE-15-DW	16W	450 mA	34-1507 lm	1210 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2118.192-ACOT-72	25W	700 mA	2873 lm	2394 lm	30°/40°/50°/55° (Lens)	3000K	90+
2118.192-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.668F-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2118.668F-LEE-15	17W	500 mA	2004 lm	1580 lm	20°/30°/45°/55° (Lens)	3000K	90+
2118.668F-LEE-15-DW	16W	450 mA	34-1507 lm	1210 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2118.668F-ACOT-72	25W	700 mA	2873 lm	2394 lm	30°/40°/50°/55° (Lens)	3000K	90+
2118.668F-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/55° (Lens)	2700-6500K	90+

Dimmable



Optional Accessory



SG7-1
Striped glass



H7-1
Honeycomb louver



DS7-1
Diffusion sheet



WG7-1
Woven glass



ACSN-17
Snoot




ACOT-82
MR16 Accessory kits




ACOT-83
GU10 Accessory kits




PJ-0079
MR16&GU10 Accessory




⊖ Cut out : 100mm (Trim)



⊖ Cut out : 100mm (Trim)



⊖ Cut out : 100mm (Trimless)





⊖ Cut out : 100mm (Trimless)

IES



Adjustable

2118.192-LEE-15
2118.668F-LEE15





H(m)	D(m)	E(lx)
20°		
1.0	0.38	7765
2.0	0.76	1941
3.0	1.14	862
4.0	1.52	485
5.0	1.90	310



Adjustable

2118.192-LEE-15
2118.668F-LEE15





H(m)	D(m)	E(lx)
30°		
1.0	0.58	5085
2.0	1.17	1271
3.0	1.75	565
4.0	2.34	317
5.0	2.92	203



Adjustable

2118.192-LEE-15
2118.668F-LEE15





H(m)	D(m)	E(lx)
45°		
1.0	0.81	2926
2.0	1.62	731
3.0	2.43	325
4.0	3.24	182
5.0	4.05	117



Adjustable

2118.192-LEE-15
2118.668F-LEE15





H(m)	D(m)	E(lx)
55°		
1.0	1.00	1987
2.0	2.01	496
3.0	3.01	220
4.0	4.02	124
5.0	5.02	79



Adjustable

2118.192-ACOT-72
2118.668F-ACOT-72





H(m)	D(m)	E(lx)
30°		
1.0	0.56	5741
2.0	1.12	1435
3.0	1.68	637
4.0	2.24	358
5.0	2.80	229



Adjustable

2118.192-ACOT-72
2118.668F-ACOT-72





H(m)	D(m)	E(lx)
40°		
1.0	0.74	5089
2.0	1.48	1272
3.0	2.22	565
4.0	2.96	318
5.0	3.70	203



Adjustable

2118.192-ACOT-72
2118.668F-ACOT-72





H(m)	D(m)	E(lx)
50°		
1.0	0.95	3567
2.0	1.89	891
3.0	2.84	396
4.0	3.79	222
5.0	4.73	142



Adjustable

2118.192-ACOT-72
2118.668F-ACOT-72



H(m)	D(m)	E(lx)
55°		
1.0	1.00	2771
2.0	2.01	692
3.0	3.01	307
4.0	4.02	173
5.0	5.02	110

STELLAR-110 Round-Adjustable

STELLAR110-RTAS
STELLAR110-RTLAS



Colours

Bezel : Black ☒ White ☐

Baffle : Black ☒ White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
Trim							
 2118.193-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2118.193-LEE-15	17W	500 mA	2004 lm	1516 lm	20°/30°/45°/55° (Lens)	3000K	90+
2118.193-LEE-15-DW	16W	450 mA	34-1507 lm	1054 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2118.193-ACOT-72	25W	700 mA	2873 lm	2118 lm	30°/40°/50°/55° (Lens)	3000K	90+
2118.193-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/55° (Lens)	2700-6500K	90+
Trimless							
 2118.669F-LEE-15A	13W	350 mA	1182 lm	-	10° (Lens)	3000K	90+
2118.669F-LEE-15	17W	500 mA	2004 lm	1516 lm	20°/30°/45°/55° (Lens)	3000K	90+
2118.669F-LEE-15-DW	16W	450 mA	34-1507 lm	1054 lm	20°/25°/40°/50° (Lens)	1800-3000K	90+
 2118.669F-ACOT-72	25W	700 mA	2873 lm	2118 lm	30°/40°/50°/55° (Lens)	3000K	90+
2118.669F-ACOT-72-WCW	22W	600 mA	2086-2304 lm	-	30°/40°/50°/55° (Lens)	2700-6500K	90+

Dimmable



Optional Accessory



SG7-1
Striped glass



H7-1
Honeycomb louver



DS7-1
Diffusion sheet



WG7-1
Woven glass




ACOT-82
MR16 Accessory kits




ACOT-83
GU10 Accessory kits




PJ-0079
MR16&GU10 Accessory




Cut out : 100mm (Trim)



Cut out : 100mm (Trim)



Cut out : 100mm (Trimless)




Cut out : 100mm (Trimless)

IES




Adjustable

2118.193-LEE-15
2118.669F-LEE15



(500mA)




H(m)	D(m)	E(lx)
20°		
1.0	0.67	7843
2.0	0.73	1961
3.0	1.10	871
4.0	1.46	490
5.0	1.83	313




Adjustable

2118.193-LEE-15
2118.669F-LEE15



(500mA)




H(m)	D(m)	E(lx)
30°		
1.0	0.58	5165
2.0	1.16	1291
3.0	1.75	573
4.0	2.33	322
5.0	2.91	206




Adjustable

2118.193-LEE-15
2118.669F-LEE15



(500mA)




H(m)	D(m)	E(lx)
45°		
1.0	0.79	2977
2.0	1.59	744
3.0	2.38	330
4.0	3.17	186
5.0	3.97	119




Adjustable

2118.193-LEE-15
2118.669F-LEE15



(500mA)




H(m)	D(m)	E(lx)
55°		
1.0	0.99	1953
2.0	1.98	488
3.0	2.97	217
4.0	3.96	122
5.0	4.95	78




Adjustable

2118.193-ACOT-72
2118.669F-ACOT-72



(700mA)




H(m)	D(m)	E(lx)
30°		
1.0	0.53	5826
2.0	1.07	1457
3.0	1.60	647
4.0	2.14	364
5.0	2.67	233




Adjustable

2118.193-ACOT-72
2118.669F-ACOT-72



(700mA)




H(m)	D(m)	E(lx)
40°		
1.0	0.72	4956
2.0	1.43	1239
3.0	2.15	550
4.0	2.87	309
5.0	3.58	198




Adjustable

2118.193-ACOT-72
2118.669F-ACOT-72



(700mA)




H(m)	D(m)	E(lx)
50°		
1.0	0.90	3453
2.0	1.81	863
3.0	2.71	383
4.0	3.61	215
5.0	4.52	138




Adjustable

2118.193-ACOT-72
2118.669F-ACOT-72



(700mA)



H(m)	D(m)	E(lx)
55°		
1.0	1.05	2616
2.0	2.10	654
3.0	3.15	290
4.0	4.21	163
5.0	5.26	104