

# ROCKET SERIES (EU)





## ROCKET Outdoor spotlight

Precision lighting, crafted for landscape design.

A minimal 4 cm form seamlessly blends into its surroundings—allowing light to take center stage.

Adjustable beam angles delicately define trees and spatial focal points.

Elevated structure avoids obstruction from planting, delivering sculptural light across trunks and foliage.

### ROCKET 戶外投射燈

#### 為景觀設計而生的精準之光

極簡 4cm 小巧設計，隱於環境，讓光成為主角。

可調投射角度，細膩勾勒樹形與空間焦點。

墊高式結構，有效避開植栽遮擋。

光束完整呈現樹幹與枝葉的雕塑光影。

## IP67

Engineered to withstand the challenges of outdoor environments, the fixture is rated IP67 for water and dust resistance. It ensures stable performance under rain, humidity, irrigation, and changing weather conditions, maintaining reliable quality for long-term landscape lighting applications.

面對戶外環境的長期考驗，燈具達到 IP67 防水防塵等級，能在雨水、濕氣、澆灌與多變氣候條件下穩定運作，確保景觀照明長時間維持可靠品質。





Reference image





### Colours

Body: Black ■ Grey ■

Article number	LED / Delivered Consumption	Voltage	Current	LED / Delivered Lumen	Beam Angle	CCT	CRI
2529.401	7.5W / 10W	AC 220-240V	200 mA	711 lm / 586 lm	18°/25°/35°/55°(Lens)	3000K	90+

Driver Built-in     



The ceiling height is 300 cm  
The light is 15 cm away from the wall.

### Optional Accessory



S-030  
Long snoot



S-028  
Asymmetrical snoot





SPIKE-1  
Ground spike

### IES





Spotlight  
2529.401



H(m)	D(m)	E(lx)
<b>18°</b>		
1.0	0.32	2641
2.0	0.63	660
3.0	0.95	293
4.0	1.27	165
5.0	1.58	105





Spotlight  
2529.401



H(m)	D(m)	E(lx)
<b>25°</b>		
1.0	0.39	2047
2.0	0.78	511
3.0	1.18	227
4.0	1.57	128
5.0	1.96	81




Spotlight  
2529.401



H(m)	D(m)	E(lx)
<b>35°</b>		
1.0	0.59	1122
2.0	1.18	280
3.0	1.77	124
4.0	2.36	70
5.0	2.95	44



Spotlight  
2529.401



H(m)	D(m)	E(lx)
<b>55°</b>		
1.0	0.97	448
2.0	1.95	112
3.0	2.92	49
4.0	3.89	28
5.0	4.87	17